



MD011A121KAB Information



For Reference Only

Part Number MD011A121KAB
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 120PF 100V NP0 2-DIP

Package 2-DIF

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MD011A121KAB Specifications

Manufacturer Part NumberMD011A121KABManufacturerAVX CorporationCategoryCapacitorsPackage2-DIPSeriesDIPGuard? MDCapacitance120pFTolerance±10%Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough Hole
Category Capacitors Ceramic Capacitors Package 2-DIP Series DIPGuard? MD Capacitance 120pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient Cog, NP0 Operating Temperature -55°C ~ 125°C Features Ratings - Applications Failure Rate - General Purpose Failure Rate
Package 2-DIP Series DIPGuard? MD Capacitance 120pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate -
Package2-DIPSeriesDIPGuard? MDCapacitance120pFTolerance±10%Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-
Series DIPGuard? MD Capacitance 120pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate -
Capacitance120pFTolerance±10%Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-
Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate -
Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate -
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate -
Features Ratings Applications General Purpose Failure Rate
Ratings - Applications General Purpose Failure Rate -
Applications General Purpose Failure Rate -
Failure Rate -
Mounting Type Through Hole
Package / Case 2-DIP
Size / Dimension 0.260" L x 0.100" W (6.60mm x 2.54mm)
Height - Seated (Max) 0.175" (4.45mm)
Thickness (Max)
Lead Spacing 0.325" (8.25mm)
Lead Style -
Report errors

MD011A121KAB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MD011A121KAB Payment Methods





















MD011A121KAB Shipping Methods













If you have any question about MD011A121KAB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com