



## **MD015A391JAB Information**



For Reference Only

Part Number MD015A391JAB
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

**Description** CAP CER 390PF 50V NP0 2-DIP

Package 2-DII

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MD015A391JAB Specifications**

Manufacturer Part Number         MD015A391JAB           Manufacturer         AVX Corporation           Category         Capacitors           Package         2-DIP           Series         DIPGuard? MD           Capacitance         390pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.100" W (6.60mm x 2.54mm)           Height - Seated (Max)         0.175" (4.45mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -		
Category         Capacitors           Package         2-DIP           Series         DIPGuard? MD           Capacitance         390pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -5°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.100" W (6.60mm x 2.54mm)           Height - Seated (Max)         0.175" (4.45mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Manufacturer Part Number	MD015A391JAB
Package         2-DIP           Series         DIPGuard? MD           Capacitance         390pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.100" W (6.60mm x 2.54mm)           Height - Seated (Max)         0.175" (4.45mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Manufacturer	AVX Corporation
Package         2-DIP           Series         DIPGuard? MD           Capacitance         390pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.100" W (6.60mm x 2.54mm)           Height - Seated (Max)         0.175" (4.45mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Category	Capacitors
Series         DIPGuard? MD           Capacitance         390pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.100" W (6.60mm x 2.54mm)           Height - Seated (Max)         0.175" (4.45mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -		Ceramic Capacitors
Capacitance       390pF         Tolerance       ±5%         Voltage - Rated       50V         Temperature Coefficient       C0G, NP0         Operating Temperature       -55°C ~ 125°C         Features       -         Ratings       -         Applications       General Purpose         Failure Rate       -         Mounting Type       Through Hole         Package / Case       2-DIP         Size / Dimension       0.260" L x 0.100" W (6.60mm x 2.54mm)         Height - Seated (Max)       0.175" (4.45mm)         Thickness (Max)       -         Lead Spacing       0.325" (8.25mm)         Lead Style       -	Package	2-DIP
Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.100" W (6.60mm x 2.54mm)           Height - Seated (Max)         0.175" (4.45mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Series	DIPGuard? MD
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.100" W (6.60mm x 2.54mm)Height - Seated (Max)0.175" (4.45mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Capacitance	390pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - COG, NPO COG, NP	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case 2-DIP Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style	Voltage - Rated	50V
Features	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.100" W (6.60mm x 2.54mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style - General Purpose	Operating Temperature	-55°C ~ 125°C
Applications General Purpose  Failure Rate -  Mounting Type Through Hole  Package / Case 2-DIP  Size / Dimension 0.260" L x 0.100" W (6.60mm x 2.54mm)  Height - Seated (Max) 0.175" (4.45mm)  Thickness (Max) -  Lead Spacing 0.325" (8.25mm)  Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.100" W (6.60mm x 2.54mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Ratings	-
Mounting Type Through Hole  Package / Case 2-DIP  Size / Dimension 0.260" L x 0.100" W (6.60mm x 2.54mm)  Height - Seated (Max) 0.175" (4.45mm)  Thickness (Max) -  Lead Spacing 0.325" (8.25mm)  Lead Style -	Applications	General Purpose
Package / Case       2-DIP         Size / Dimension       0.260" L x 0.100" W (6.60mm x 2.54mm)         Height - Seated (Max)       0.175" (4.45mm)         Thickness (Max)       -         Lead Spacing       0.325" (8.25mm)         Lead Style       -	Failure Rate	-
Size / Dimension       0.260" L x 0.100" W (6.60mm x 2.54mm)         Height - Seated (Max)       0.175" (4.45mm)         Thickness (Max)       -         Lead Spacing       0.325" (8.25mm)         Lead Style       -	Mounting Type	Through Hole
Height - Seated (Max)       0.175" (4.45mm)         Thickness (Max)       -         Lead Spacing       0.325" (8.25mm)         Lead Style       -	Package / Case	2-DIP
Thickness (Max)  Lead Spacing  0.325" (8.25mm)  Lead Style  -	Size / Dimension	0.260" L x 0.100" W (6.60mm x 2.54mm)
Lead Spacing         0.325" (8.25mm)           Lead Style         -	Height - Seated (Max)	0.175" (4.45mm)
Lead Style -	Thickness (Max)	-
	Lead Spacing	0.325" (8.25mm)
Report errors?	Lead Style	-
		Report errors?

#### **MD015A391JAB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **MD015A391JAB Payment Methods**





















## **MD015A391JAB Shipping Methods**













If you have any question about MD015A391JAB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com