

# MDF7-10S-2.54DSA(56)

#### MDF7-10S-2.54DSA(56) Information

| () Hei   | sener.com<br>ar arrect batta there | MDF7-10S-2.54DSA(56)<br>Hirose Electric Co Ltd<br>Connectors, Interconnects<br>Rectangular Connectors - Headers, Receptacles,<br>Female Sockets<br>CONN RECEPT 10POS SINGLE TIN |                 |
|----------|------------------------------------|---|-----------------|
| For Refe | erence Only                        | For the pricing/inventory/lead time, please contact us  |                 |
| Por Refe | fience Only                        | Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com   | Request a Quote |

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## MDF7-10S-2.54DSA(56) Specifications

| Manufacturer Part Number          | MDF7-10S-2.54DSA(56)  |
|-----------------------------------|---|
| Manufacturer                      | Hirose Electric Co Ltd  |
| Category                          | Connectors, Interconnects                                     |
|                                   | Rectangular Connectors - Headers, Receptacles, Female Sockets |
| Package                           | -   |
| Series                            | MDF7  |
| Connector Type                    | Receptacle, Bottom Entry                                      |
| Contact Type                      | Female Socket   |
| Style                             | Board to Board  |
| Number of Positions               | 10  |
| Number of Positions Loaded        | All   |
| Pitch - Mating                    | 0.100" (2.54mm)   |
| Number of Rows                    | 1   |
| Row Spacing - Mating              | -   |
| Mounting Type                     | Through Hole  |
| Termination                       | Solder  |
| Fastening Type                    | Push-Pull   |
| Contact Finish - Mating           | Gold  |
| Contact Finish Thickness - Mating | 8μin (0.20μm)   |
| Insulation Color                  | Black   |
| Insulation Height                 | 0.197" (5.00mm)   |
| Contact Length - Post             | 0.118" (3.00mm)   |
| Operating Temperature             | -35°C ~ 85°C  |
| Material Flammability Rating      | UL94 V-0  |
|                                   |   |

| Contact Finish - Post  | Tin            |
|------------------------|----------------|
| Mated Stacking Heights | -              |
| Ingress Protection     | -              |
| Features               | -              |
|                        | Report errors? |

#### MDF7-10S-2.54DSA(56) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

# MDF7-10S-2.54DSA(56) Payment Methods WIRE transfer PayPal Wise MoneyGram Alipay: VISA MoneyGram MDF7-10S-2.54DSA(56) Shipping Methods



If you have any question about MDF7-10S-2.54DSA(56), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com