

MDF7-48D-2.54DSA(55)

MDF7-48D-2.54DSA(55) Information

Heisener.com		MDF7-48D-2.54DSA(55) Hirose Electric Co Ltd Connectors, Interconnects Rectangular Connectors - Headers, Receptacles,	
	Description	Female Sockets CONN RCPT 48POS 2.54MM	
	Package	-	回胡振辩的
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MDF7-48D-2.54DSA(55) Specifications

Manufacturer Part NumberMDF7-48D-2.54DSA(55)ManufacturerHirose Electric Co LtdCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMDF7Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions LoadedAllNumber of Positions Loaded0.100" (2.54mm)Number of Ross0.100" (2.54mm)Number of Ross0.100" (2.54mm)Row Spacing - MatingSolderMounting TypeThrough HoleContact Finish - MatingSolderRotter Finish - MatingSolderRossening TypeInformationStating TypeSolderFinish - MatingSolderRossening TypeSolderRossening TypeSolderFinish - MatingSolderStating TypeSolderFinish - MatingSolderStating TypeSolderFinish - MatingSolderSolder Finish - MatingSolderStation ColorBackStation ColorSolderStation Finish - MatingSolderSolder Finish - MatingSolderSolder Finish - MatingSolderSolder SolderSolderSolder SolderSolderSolder SolderSolderSolder SolderSolderSolder SolderSolderSolder SolderSolderSolder Solde		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMDF7Connector TypeReceptacle, Bottom EntryConnector TypeFemale SocketStyleBoard to BoardNumber of Positions48Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeNoldelFreminationSolderFreminationSolderForther ShaftingInsolationContact Finish - MatingTinContact Finish - MatingSolderFunding TypeBackInsulation ColorBlackInsulation Finish - Mating100° (2.50mm)	Manufacturer Part Number	MDF7-48D-2.54DSA(55)
Actangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMDF7Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions48Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating7inContact Finish Thickness - Mating7inInsulation ColorBlackInsulation Height0.197° (5.00mm)	Manufacturer	Hirose Electric Co Ltd
Package-SeriesMDF7Conactor TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions48Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingSolderContact Finish - MatingSolderInnulation ColorSn/in (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Category	Connectors, Interconnects
SeriesMDF7Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions48Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypePush-PullContact Finish - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions48Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeOnlon" (2.54mm)FareminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - MatingBlackInsulation ColorJ.019" (5.00mm)	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions48Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating88.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Series	MDF7
StyleBoard to BoardNumber of Positions48Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Connector Type	Receptacle, Bottom Entry
Number of Positions48Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation HeightJol9" (5.00mm)	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Number of Positions	48
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish - Mating88.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Mounting Type	Through Hole
Contact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Termination	Solder
Contact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorBlackInsulation Height0.197" (5.00mm)	Fastening Type	Push-Pull
Insulation Color Black Insulation Height 0.197" (5.00mm)	Contact Finish - Mating	Tin
Insulation Height 0.197" (5.00mm)	Contact Finish Thickness - Mating	78.7µin (2.00µm)
-	Insulation Color	Black
Contact Length - Post 0.118" (3.00mm)	Insulation Height	0.197" (5.00mm)
	Contact Length - Post	0.118" (3.00mm)
Operating Temperature $-35^{\circ}C \sim 85^{\circ}C$	Operating Temperature	-35°C ~ 85°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about MDF7-48D-2.54DSA(55), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com