



MDS-090AAS19 BA Information



For Reference Only

Part Number MDS-090AAS19 BA
Manufacturer Delta Electronics

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 19V 90W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MDS-090AAS19 BA Specifications

Manufacturer Part Number MDS-090AAS19 BA Manufacturer Delta Electronics Category Power Supplies - External/Internal (Off-Board) Package - Series MDS Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.7A Power (Watts) 89W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series MDS Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.7A Power (Watts) 89W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Manufacturer Part Number	MDS-090AAS19 BA
Package-SeriesMDSRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)4.7APower (Watts)89WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorPower DIN, 4 PinSize / Dimension5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Manufacturer	Delta Electronics
Package - Series MDS Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.7A Power (Watts) 89W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesMDSRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)4.7APower (Watts)89WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorPower DIN, 4 PinSize / Dimension5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output19VCurrent - Output (Max)4.7APower (Watts)89WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorPower DIN, 4 PinSize / Dimension5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.7A Power (Watts) 89W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Series	MDS
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 19V Current - Output (Max) 4.7A Power (Watts) 89W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 19V Current - Output (Max) 4.7A Power (Watts) 89W No Load Power Consumption 500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $5.91^{\circ}\text{L x } 2.36^{\circ}\text{W x } 1.38^{\circ}\text{H } (150.0\text{mm x } 60.0\text{mm x } 35.0\text{mm})$	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 4.7A Power (Watts) 89W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 19V 4.7A 4.7A 4.7A 89W Commercial), Medical 4.7A - 4.7A 89W Commercial), Medical 4.7A - 4.7A 89W Commercial), Medical 4.7A - 4.7A 89W Commercial), Medical 4.7A - 4.7A 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 4.7A Power (Watts) 89W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 89W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Voltage - Output	19V
No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Current - Output (Max)	4.7A
Polarization - Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Power (Watts)	89W
Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $5.91^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.38^{\circ}\text{H} (150.0 \text{mm} \times 35.0 \text{mm})$	No Load Power Consumption	500mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $5.91^{\circ}\text{L} \times 2.36^{\circ} \text{W} \times 1.38^{\circ} \text{H} (150.0 \text{mm} \times 35.0 \text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $5.91^{\circ}\text{L} \times 2.36^{\circ}\text{W} \times 1.38^{\circ}\text{H} (150.0\text{mm} \times 60.0\text{mm} \times 35.0\text{mm})$	Applications	ITE (Commercial), Medical
Output Connector Power DIN, 4 Pin Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Efficiency	Level VI
Size / Dimension 5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	5.91" L x 2.36" W x 1.38" H (150.0mm x 60.0mm x 35.0mm)
		Report errors?

MDS-090AAS19 BA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MDS-090AAS19 BA Payment Methods





















MDS-090AAS19 BA Shipping Methods













If you have any question about MDS-090AAS19 BA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com