



### **ME1801K25JHF Information**

Heisener.com

Part Number ME1801K25JHF

Manufacturer TE Connectivity Passive Product

Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 1.25K OHM 5% 230W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ME1801K25JHF Specifications**

Manufacturer Part Number         ME1801K25JHF           Manufacturer         TE Connectivity Passive Product           Category         Resistors           Package         Radial, Tubular           Series         ME, CGS           Resistance         1.25 kOhms           Tolerance         ±5%           Power (Watts)         230W           Composition         Wirewound           Temperature Coefficient         ±400ppm/°C           Operating Temperature         -55°C ~ 200°C           Features         -           Coating, Housing Type         Vitreous Enamel Coated           Mounting Feature         Brackets (not included)           Size / Dimension         1.102" Dia x 8.504" L (28.00mm x 216.00mm)           Height - Seated (Max)         -           Lead Style         Solder Lugs           Package / Case         Radial, Tubular           Failure Rate         -		
CategoryResistorsPackageRadial, TubularSeriesME, CGSResistance1.25 kOhmsTolerance±5%Power (Watts)230WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.102" Dia x 8.504" L (28.00mm x 216.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	ME1801K25JHF
Chassis Mount Resistors  Package Radial, Tubular  Series ME, CGS  Resistance 1.25 kOhms  Tolerance ±5%  Power (Watts) 230W  Composition Wirewound  Temperature Coefficient ±400ppm/°C  Operating Temperature -55°C ~ 200°C  Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 1.102" Dia x 8.504" L (28.00mm x 216.00mm)  Height - Seated (Max) - Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Manufacturer	TE Connectivity Passive Product
PackageRadial, TubularSeriesME, CGSResistance1.25 kOhmsTolerance±5%Power (Watts)230WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.102" Dia x 8.504" L (28.00mm x 216.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesME, CGSResistance1.25 kOhmsTolerance±5%Power (Watts)230WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.102" Dia x 8.504" L (28.00mm x 216.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance1.25 kOhmsTolerance±5%Power (Watts)230WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.102" Dia x 8.504" L (28.00mm x 216.00mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5%  Power (Watts) 230W  Composition Wirewound  Temperature Coefficient ±400ppm/°C  Operating Temperature -55°C ~ 200°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 1.102" Dia x 8.504" L (28.00mm x 216.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Series	ME, CGS
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±400ppm/°C  Operating Temperature  -55°C ~ 200°C  Features  - Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  1.102" Dia x 8.504" L (28.00mm x 216.00mm)  Height - Seated (Max)  - Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Resistance	1.25 kOhms
Composition Wirewound  Temperature Coefficient ±400ppm/°C  Operating Temperature -55°C ~ 200°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 1.102" Dia x 8.504" L (28.00mm x 216.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Tolerance	±5%
Temperature Coefficient ±400ppm/°C  Operating Temperature -55°C ~ 200°C  Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 1.102" Dia x 8.504" L (28.00mm x 216.00mm)  Height - Seated (Max) - Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate	Power (Watts)	230W
Operating Temperature  -55°C ~ 200°C  Features  - Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  1.102" Dia x 8.504" L (28.00mm x 216.00mm)  Height - Seated (Max)  - Lead Style  Solder Lugs  Package / Case  Radial, Tubular  Failure Rate  - Solder Lugs	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 1.102" Dia x 8.504" L (28.00mm x 216.00mm)  Height - Seated (Max) - Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate	Temperature Coefficient	±400ppm/°C
Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  1.102" Dia x 8.504" L (28.00mm x 216.00mm)  Height - Seated (Max)  - Lead Style  Package / Case  Radial, Tubular  Failure Rate  Vitreous Enamel Coated  Brackets (not included)  1.102" Dia x 8.504" L (28.00mm x 216.00mm)  - Lead Style  Solder Lugs  Radial, Tubular	Operating Temperature	-55°C ~ 200°C
Mounting Feature Brackets (not included) Size / Dimension 1.102" Dia x 8.504" L (28.00mm x 216.00mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Features	-
Size / Dimension 1.102" Dia x 8.504" L (28.00mm x 216.00mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.102" Dia x 8.504" L (28.00mm x 216.00mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

#### **ME1801K25JHF Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **ME1801K25JHF Payment Methods**



















### **ME1801K25JHF Shipping Methods**













If you have any question about ME1801K25JHF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com