



MED0600 Information



For Reference Only

Part Number MED0600
Manufacturer Amgis, LLC
Category Transformers
Power Transformers

Description XFRMR TOROIDAL 600VA

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MED0600 Specifications

Manufacturer Part Number Manufacturer Category Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers		
Category Transformers Power Transformers Package - Series - Type Toroidal Voltage - Primary Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 600 VA Mounting Type - Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Transformers Tornination Style Toroidal Nov, 120V Parallel 120V, Series 240V Parallel 5A, Series 2.5A Primary Winding(s) Dual Williple Taps No 600 VA 600 VA 600 VA 600 VA 600 VA 600 VA Fermination Style Ferminati	Manufacturer Part Number	MED0600
Package - Ceries - Toroidal - Tor	Manufacturer	Amgis, LLC
Package-Series-TypeToroidalVoltage - Primary100V, 120VVoltage - Secondary (Full Load)Parallel 120V, Series 240VCurrent - Output (Max)Parallel 5A, Series 2.5APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max600 VAMounting Type-Termination StyleWire LeadsSize / Dimension-Height - Seated (Max)66.04mmVoltage - Isolation-Weight12 lbs (5.4kg)	Category	Transformers
Series-TypeToroidalVoltage - Primary100V, 120VVoltage - Secondary (Full Load)Parallel 120V, Series 240VCurrent - Output (Max)Parallel 5A, Series 2.5APrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)DualCenter TapNoPower - Max600 VAMounting Type-Termination StyleWire LeadsSize / Dimension-Height - Seated (Max)66.04mmVoltage - Isolation-Weight12 lbs (5.4kg)		Power Transformers
Type Toroidal Voltage - Primary 100V, 120V Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 600 VA Mounting Type - Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 66.04mm Voltage - Isolation - Weight 12 lbs (5.4kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Center Tap No Power - Max 600 VA Mounting Type Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 100V, 120V Parallel 120V, Series 240V Parallel 5A, Series 2.5A Primary Winding(s) Dual, Multiple Taps No Wue Leads 66.04mm - 12 lbs (5.4kg)	Series	-
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 600 VA Mounting Type - Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 120V, Series 240V Parallel 15A, Series 2.5A Primary Winding(s) Dual No 600 VA Mounting Type - 12 lbs (5.4kg)	Type	Toroidal
Current - Output (Max) Parallel 5A, Series 2.5A Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Dual Center Tap No Power - Max 600 VA Mounting Type - Termination Style Wire Leads Size / Dimension - Height - Seated (Max) Voltage - Isolation - Weight 12 lbs (5.4kg)	Voltage - Primary	100V, 120V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 600 VA Mounting Type - Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Veight Dual, Multiple Taps Dual No 66.04MM 12 lbs (5.4kg)	Voltage - Secondary (Full Load)	Parallel 120V, Series 240V
Secondary Winding(s)DualCenter TapNoPower - Max600 VAMounting Type-Termination StyleWire LeadsSize / Dimension-Height - Seated (Max)66.04mmVoltage - Isolation-Weight12 lbs (5.4kg)	Current - Output (Max)	Parallel 5A, Series 2.5A
Center Tap No Power - Max 600 VA Mounting Type - Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 66.04mm Voltage - Isolation - Weight 12 lbs (5.4kg)	Primary Winding(s)	Dual, Multiple Taps
Power - Max 600 VA Mounting Type - Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 66.04mm Voltage - Isolation - Weight 12 lbs (5.4kg)	Secondary Winding(s)	Dual
Mounting Type - Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 66.04mm Voltage - Isolation - Weight 12 lbs (5.4kg)	Center Tap	No
Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 66.04mm Voltage - Isolation - Weight 12 lbs (5.4kg)	Power - Max	600 VA
Size / Dimension - Height - Seated (Max) 66.04mm Voltage - Isolation - Weight 12 lbs (5.4kg)	Mounting Type	-
Height - Seated (Max) Voltage - Isolation Weight 66.04mm - 12 lbs (5.4kg)	Termination Style	Wire Leads
Voltage - Isolation - Weight 12 lbs (5.4kg)	Size / Dimension	-
Weight 12 lbs (5.4kg)	Height - Seated (Max)	66.04mm
	Voltage - Isolation	-
Report errors?	Weight	12 lbs (5.4kg)
10000		Report errors?

MED0600 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MED0600 Payment Methods



















MED0600 Shipping Methods













If you have any question about MED0600, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com