

MENB1010A0340N01

MENB1010A0340N01 Information

Heisener.com Octation ce cantiner	Part Number Manufacturer Category Description Package	MENB1010A0340N01 SL Power Electronics Manufacture of Condor/Ault Brands Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC DESKTOP ADAPTER 3V 10W	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MENB1010A0340N01 Specifications

Manufacturer Part NumberMENB1010A0340N01ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB1010Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input30% - 240 VACVoltage - Output (Max)33APower (Watts)100% (Max)PolarizationSolomW (Max)PolarizationSolomW (Max)ApplicationsLevel VOperating Temperature0°C ~ 40°COutput ConnectorBartel Plug KA, 2.1mn I.D. x 5.5mn O.D. x 9.5mm		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB1010Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output (Max)33APower (Watts)100WNo Load Power Consumption300mW (Max)PolarizationDositive CenterApplicationsKeicalOperating Temperature0°C ~ 40°COutput ConnectorBartel Plug KA, 2.1mm LD, x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Manufacturer Part Number	MENB1010A0340N01
AC DC Desktop, Wall AdaptersPackage-SeriesMENB1010Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output3VCurrent - Output (Max)3.33APower (Watts)10WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsKeicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dinension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesMENB1010Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output3/VCurrent - Output (Max)3.33APower (Watts)100W (Max)PolarizationSoliwe CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series MENB1010 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 3V Current - Output (Max) 3.33A Power (Watts) 100W (Max) No Load Power Consumption 300mW (Max) Polarization Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output3VCurrent - Output (Max)3.3APower (Watts)100 ~ 240 WACNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBartel Plug R/A, 2.1mm I.D. x. 5.5mm O.D. x. 9.5mmSize / Dimension3.00° L x. 1.85° W x. 1.26° H (84.0mm x. 47.0mm x. 32.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 3V Current - Output (Max) 3.33A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.0" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Series	MENB1010
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 3V Current - Output (Max) 3.33A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Region Utilized	International
Voltage - Input100 ~ 240 VACVoltage - Output3VCurrent - Output (Max)3.33APower (Watts)10WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Form	Desktop (Class II)
Voltage - Output3VCurrent - Output (Max)3.33APower (Watts)10WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)3.33APower (Watts)10WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)10WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Voltage - Output	3V
No Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Current - Output (Max)	3.33A
PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Power (Watts)	10W
ApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	No Load Power Consumption	300mW (Max)
EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Polarization	Positive Center
Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Applications	Medical
Output ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Efficiency	Level V
Size / Dimension 3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Operating Temperature	0° C ~ 40° C
	Output Connector	Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
	Size / Dimension	3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)
Report error		Report errors?

MENB1010A0340N01 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MENB1010A0340N01 Payment Methods



If you have any question about MENB1010A0340N01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com