

MENB1010A0703F01

MENB1010A0703F01 Information

Man Cate	AC DC Desktop, Wall Adapters ription AC/DC DESKTOP ADAPTER 7.5V 10W	
For Reference Only	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MENB1010A0703F01 Specifications

Manufacturer Part NumberMENB1010A0703F01Manufacturer Part NumberSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)Rackage-Package-SeriesMENB1010Region UtilizedInternationalFormDesktop (Class I)Yoltage - InputCord (Sold Separately)Voltage - Output0.0 ~ 240 VACYoltage - Output (Max)1.6APower (Watts)1.6APower (Watts)300m (Max)PolarizationPositive CenterApplicationsMeidaPoperating Temperature0°C ~ 40°COutput ConnectorBarel Plug. 2.5mm I.D. x.5.5mm O.D. x.9.5mmSize / Dimension3.0" Lx 1.85" Wx 1.26" H (84.0mm x 47.0mm x 32.0mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB1010Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output (Max)1.6APower (Watts)100m (Max)PolarizationSoliw CenterApplicationsMedicalEfficiencyCerc 40°COutput ConnectorBartel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Manufacturer Part Number	MENB1010A0703F01
AC DC Desktop, Wall AdaptersPackage-SeriesMENB1010Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output7.5VCurrent - Output (Max)1.6APower (Watts)300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package.SeriesMENB1010Region UtilizedInternationalFormDesktop Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output7.5VCurrent - Output (Max)1.6APower (Watts)300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBartel Plug 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series MENB1010 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 1.6A Power (Watts) 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output7.5VCurrent - Output (Max)1.6APower (Watts)300mW (Max)No Load Power Consumption300mW (Max)PolarizationMedicalApplicationsKevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.00° L x 1.85° W x 1.26° H (84.0mm x 47.0mm x 32.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 1.6A Power (Watts) 12W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.0" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Series	MENB1010
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 7.5V Current - Output (Max) 1.6A Power (Watts) 12W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Region Utilized	International
Voltage - Input100 ~ 240 VACVoltage - Output7.5VCurrent - Output (Max)1.6APower (Watts)12WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Form	Desktop (Class I)
Voltage - Output7.5VCurrent - Output (Max)1.6APower (Watts)12WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)1.6APower (Watts)12WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)12WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Voltage - Output	7.5V
No Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Current - Output (Max)	1.6A
PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Power (Watts)	12W
ApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	No Load Power Consumption	300mW (Max)
EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Polarization	Positive Center
Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Applications	Medical
Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Efficiency	Level V
Size / Dimension 3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)	Operating Temperature	0° C ~ 40° C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
	Size / Dimension	3.30" L x 1.85" W x 1.26" H (84.0mm x 47.0mm x 32.0mm)
Report erro		Report errors?

MENB1010A0703F01 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MENB1010A0703F01 Payment Methods





If you have any question about MENB1010A0703F01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com