

# **MENB1030A1403F01**

## MENB1030A1403F01 Information

Contraction for the second sec	Part Number Manufacturer Category Description Package	MENB1030A1403F01 SL Power Electronics Manufacture of Condor/Ault Brands Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC DESKTOP ADAPTER 14V 30W	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# MENB1030A1403F01 Specifications

Manufacturer Part NumberMENB1030A1403F01ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output (Max)2.1APower (Watts)29WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output14VCurrent - Output (Max)2.1APower (Watts)99WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Manufacturer Part Number	MENB1030A1403F01
AC DC Desktop, Wall AdaptersPackage-SeriesMENB 1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output14VCurrent - Output (Max)2.1APower (Watts)29WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output14VCurrent - Output (Max)29WPower (Watts)100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOutput Connector20°C ~ 40°COutput ConnectorBartel Plag. 2.5mm LD. x 5.5mm OD. x 9.5mm	Category	Power Supplies - External/Internal (Off-Board)
SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output14VCurrent - Output (Max)2.1APower (Watts)9WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsLevel VEfficiencyLevel VOutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output14VCurrent - Output (Max)2.1APower (Watts)29WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsKedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBartel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Package	-
FormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output14VCurrent - Output (Max)2.1APower (Watts)29WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Series	MENB1030
Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output14VCurrent - Output (Max)2.1APower (Watts)29WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Region Utilized	International
Voltage - Input100 ~ 240 VACVoltage - Output14VCurrent - Output (Max)2.1APower (Watts)29WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Form	Desktop (Class I)
Voltage - Output14VCurrent - Output (Max)2.1APower (Watts)29WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Input Type	Cord (Sold Separately)
Current - Output (Max)2.1APower (Watts)29WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Voltage - Input	100 ~ 240 VAC
Power (Watts)29WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Voltage - Output	14V
No Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Current - Output (Max)	2.1A
PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Power (Watts)	29W
ApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	No Load Power Consumption	100mW (Max)
EfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Polarization	Positive Center
Operating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Applications	Medical
Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Efficiency	Level V
	Operating Temperature	$-20^{\circ}\text{C} \sim 40^{\circ}\text{C}$
Size / Dimension 3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm)	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
	Size / Dimension	3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm)
Report error		Report errors?

### MENB1030A1403F01 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MENB1030A1403F01 Payment Methods





If you have any question about MENB1030A1403F01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com