

MENB1030A1802F01

MENB1030A1802F01 Information

| For Reference Only | Part Number Manufacturer Category | MENB1030A1802F01 SL Power Electronics Manufacture of Condor/Ault Brands Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters | |
|--------------------|---|---|-----------------|
| | Description | AC/DC DESKTOP ADAPTER 18V 30W | |
| | Package | - | |
| | | For the pricing/inventory/lead time, please contact | |
| | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MENB1030A1802F01 Specifications

| Manufacturer Part Number MENB 1030A 1802F01 Manufacturer SL Power Electronics Manufacture of Condor/Ault Brands Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC DC Desktop, Wall Adapters Package - Series MENB 1030 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 1.67A Power (Watts) 30W No Load Power Consumption 100mW (Max) Polarization Medical Efficiency Level V Operating Temperature -20°C ~ 40°C Output Connector Bartel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension Sarcel Y.L. 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | | |
|---|---------------------------|--|
| CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB 1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Manufacturer Part Number | MENB1030A1802F01 |
| AC DC Desktop, Wall AdaptersPackage-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm x 31.0mm) | Manufacturer | SL Power Electronics Manufacture of Condor/Ault Brands |
| Package-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Category | Power Supplies - External/Internal (Off-Board) |
| SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | | AC DC Desktop, Wall Adapters |
| Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Package | - |
| Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 18V Current - Output (Max) 1.67A Power (Watts) 30W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature -20°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Series | MENB1030 |
| Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 18V Current - Output (Max) 1.67A Power (Watts) 30W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature -20°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Region Utilized | International |
| Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Form | Desktop (Class I) |
| Voltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 31.0mm) | Input Type | Cord (Sold Separately) |
| Current - Output (Max) 1.67A Power (Watts) 30W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature -20°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Voltage - Input | 100 ~ 240 VAC |
| Power (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Voltage - Output | 18V |
| No Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Current - Output (Max) | 1.67A |
| PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Power (Watts) | 30W |
| ApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | No Load Power Consumption | 100mW (Max) |
| ITEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Polarization | Positive Center |
| Operating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Applications | Medical |
| Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Efficiency | Level V |
| Size / Dimension 3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) | Operating Temperature | -20°C ~ 40°C |
| | Output Connector | Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm |
| Report errors | Size / Dimension | 3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) |
| | | Report errors? |

MENB1030A1802F01 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MENB1030A1802F01 Payment Methods





If you have any question about MENB1030A1802F01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com