

# MENB1030A1803F01

## MENB1030A1803F01 Information

| Heisener.com       | Part Number<br>Manufacturer<br>Category<br>Description<br>Package | MENB1030A1803F01<br>SL Power Electronics Manufacture of Condor/Ault<br>Brands<br>Power Supplies - External/Internal (Off-Board)<br>AC DC Desktop, Wall Adapters<br>AC/DC DESKTOP ADAPTER 18V 30W |                 |
|--------------------|---|--|-----------------|
| For Reference Only |   | For the pricing/inventory/lead time, please contact<br>us<br>Website: https://www.heisener.com   | Request a Quote |

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# MENB1030A1803F01 Specifications

| Manufacturer Part NumberMENB 1030A 1803F01ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB 1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm |                           |  |
|--|---------------------------|--|
| CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output1.8VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C   | Manufacturer Part Number  | MENB1030A1803F01                                       |
| AC DC Desktop, Wall AdaptersPackage-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C  | Manufacturer              | SL Power Electronics Manufacture of Condor/Ault Brands |
| Package-SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C  | Category                  | Power Supplies - External/Internal (Off-Board)         |
| SeriesMENB1030Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C  |                           | AC DC Desktop, Wall Adapters                           |
| Region UtilizedInternationalRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C  | Package                   | -  |
| FormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C  | Series                    | MENB1030   |
| Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C   | Region Utilized           | International  |
| Voltage - Input100 ~ 240 VACVoltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C   | Form                      | Desktop (Class I)                                      |
| Voltage - Output18VCurrent - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C   | Input Type                | Cord (Sold Separately)                                 |
| Current - Output (Max)1.67APower (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C  | Voltage - Input           | 100 ~ 240 VAC  |
| Power (Watts)30WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C   | Voltage - Output          | 18V  |
| No Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C   | Current - Output (Max)    | 1.67A  |
| PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C   | Power (Watts)             | 30W  |
| ApplicationsMedicalEfficiencyLevel VOperating Temperature-20°C ~ 40°C  | No Load Power Consumption | 100mW (Max)  |
| Efficiency Level V   Operating Temperature -20°C ~ 40°C  | Polarization              | Positive Center  |
| Operating Temperature $-20^{\circ}\text{C} \sim 40^{\circ}\text{C}$  | Applications              | Medical  |
| -tt  | Efficiency                | Level V  |
| Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  | Operating Temperature     | $-20^{\circ}\text{C} \sim 40^{\circ}\text{C}$          |
|  | Output Connector          | Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           |
| Size / Dimension 3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm)  | Size / Dimension          | 3.76" L x 2.13" W x 1.22" H (95.5mm x 54.0mm x 31.0mm) |
| Report error   |                           | Report errors?   |

### MENB1030A1803F01 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MENB1030A1803F01 Payment Methods





If you have any question about MENB1030A1803F01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com