

MF-LR600 Information

Heisener.com

Part Number MF-LR600

Manufacturer Bourns Inc.

Category Circuit Protection
PTC Resettable Fuses

Description FUSE RESETTABLE LOW RESISTANCE

Package Strap

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MF-LR600 Specifications

Manufacturer Part Number MF-LR600 Manufacturer Bourns Inc. Category Circuit Protection Package Strap Series Multifuse?, MF-LR Type Polymeric Voltage - Max 10V Current - Max 100A Current - Hold (Ih) (Max) 6A Current - Trip (It) 11.7A Time to Trip 5s Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm) Height - Seated (Max) -	THE ELECTION SPECIALISMS	
Category Circuit Protection Package Strap Series Multifuse?, MF-LR Type Polymeric Voltage - Max 10V Current - Max 100A Current - Hold (lh) (Max) 6A Current - Trip (lt) 11.7A Time to Trip 5s Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)	Manufacturer Part Number	MF-LR600
PTC Resettable Fuses Package Strap Series Multifuse?, MF-LR Type Polymeric Voltage - Max 10V Current - Max 100A Current - Hold (Ih) (Max) 6A Current - Trip (It) 11.7A Time to Trip 5s Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)	Manufacturer	Bourns Inc.
Package Strap Series Multifuse?, MF-LR Type Polymeric Voltage - Max 10V Current - Max 100A Current - Hold (lh) (Max) 6A Current - Trip (lt) 11.7A Time to Trip 5s Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)	Category	Circuit Protection
Series Multifuse?, MF-LR Type Polymeric Voltage - Max 10V Current - Max 100A Current - Hold (lh) (Max) 6A Current - Trip (It) 11.7A Time to Trip 5s Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)		PTC Resettable Fuses
Type Polymeric Voltage - Max 10V Current - Max 100A Current - Hold (lh) (Max) 6A Current - Trip (lt) 11.7A Time to Trip 5s Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)	Package	Strap
Voltage - Max Current - Max 100A Current - Hold (Ih) (Max) 6A Current - Trip (It) 11.7A Time to Trip 5s Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings Nounting Type User Defined Package / Case Size / Dimension 10V 10V 10V 10V 10V 10V 10V 11.7A 11.7	Series	Multifuse?, MF-LR
Current - Max Current - Hold (Ih) (Max) 6A Current - Trip (It) 11.7A Time to Trip 5s Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Size / Dimension 100A 100A 100A 100A 100A 100A 100A 100	Type	Polymeric
Current - Hold (Ih) (Max) Current - Trip (It) 11.7A Time to Trip 5s Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Size / Dimension 6A 11.7A 11.7A 7 mOhms 7 mOhms 19 mOhms 19 mOhms - User Defined 0.984" L x 0.587" W (25.00mm x 14.90mm)	Voltage - Max	10V
Current - Trip (It) Time to Trip Ss Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature Auore - 40°C ~ 85°C Ratings - User Defined Package / Case Size / Dimension 11.7A 11.7A	Current - Max	100A
Time to Trip Ss Resistance - Initial (Ri) (Min) 7 mOhms Resistance - Post Trip (R1) (Max) 19 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 5 s V mOhms User Defined 0.984" L x 0.587" W (25.00mm x 14.90mm)	Current - Hold (Ih) (Max)	6A
Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Size / Dimension 7 mOhms 19 mOhms - User Defined 0.984" L x 0.587" W (25.00mm x 14.90mm)	Current - Trip (It)	11.7A
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 19 mOhms - User Defined 0.984" L x 0.587" W (25.00mm x 14.90mm)	Time to Trip	5s
Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension O.984" L x 0.587" W (25.00mm x 14.90mm)	Resistance - Initial (Ri) (Min)	7 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type User Defined Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)	Resistance - Post Trip (R1) (Max)	19 mOhms
Ratings - User Defined Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)	Resistance - 25°C (Typ)	-
Mounting Type User Defined Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)	Operating Temperature	-40°C ~ 85°C
Package / Case Strap Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)	Ratings	-
Size / Dimension 0.984" L x 0.587" W (25.00mm x 14.90mm)	Mounting Type	User Defined
	Package / Case	Strap
Height - Seated (Max)	Size / Dimension	0.984" L x 0.587" W (25.00mm x 14.90mm)
	Height - Seated (Max)	-
Thickness (Max) 0.039" (1.00mm)	Thickness (Max)	0.039" (1.00mm)
Lead Spacing -	Lead Spacing	-
Report errors?		Report errors?

MF-LR600 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MF-LR600 Payment Methods





















MF-LR600 Shipping Methods













If you have any question about MF-LR600, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com