

MF-R015/600-B-2 Information



For Reference Only

Part Number MF-R015/600-B-2

Manufacturer Bourns Inc.

Category Circuit Protection

PTC Resettable Fuses

Description FUSE PTC RESETTABLE

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MF-R015/600-B-2 Specifications

Manufacturer Part Number MF-R015/600-B-2 Manufacturer Bourns Inc. Category Circuit Protection PTC Resettable Fuses Package Radial, Disc Series Multifuse?, MF-R/600 Type Polymeric Voltage - Max 250V (600V Int) Current - Max 3A Current - Hold (lh) (Max) 150mA Current - Trip (lt) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)		
Category Circuit Protection Package Radial, Disc Series Multifuse?, MF-R/600 Type Polymeric Voltage - Max 250V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 150mA Current - Trip (It) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Manufacturer Part Number	MF-R015/600-B-2
PTC Resettable Fuses Package Radial, Disc Series Multifuse?, MF-R/600 Type Polymeric Voltage - Max 250V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 150mA Current - Trip (It) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Manufacturer	Bourns Inc.
Package Radial, Disc Series Multifuse?, MF-R/600 Type Polymeric Voltage - Max 250V (600V Int) Current - Max 3A Current - Hold (lh) (Max) 150mA Current - Trip (It) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Category	Circuit Protection
Series Multifuse?, MF-R/600 Type Polymeric Voltage - Max 250V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 150mA Current - Trip (It) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)		PTC Resettable Fuses
Type Polymeric Voltage - Max 250V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 150mA Current - Trip (It) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Package	Radial, Disc
Voltage - Max 250V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 150mA Current - Trip (It) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Series	Multifuse?, MF-R/600
Current - Max 3A Current - Hold (lh) (Max) 150mA Current - Trip (It) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Type	Polymeric
Current - Hold (Ih) (Max) 150mA Current - Trip (It) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Voltage - Max	250V (600V Int)
Current - Trip (It) 300mA Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Current - Max	3A
Time to Trip 5s Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Current - Hold (Ih) (Max)	150mA
Resistance - Initial (Ri) (Min) 9 Ohms Resistance - Post Trip (R1) (Max) 22 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Current - Trip (It)	300mA
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 1- Lead Spacing 0.197" (5.00mm)	Time to Trip	5s
Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Resistance - Initial (Ri) (Min)	9 Ohms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Resistance - Post Trip (R1) (Max)	22 Ohms
Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Resistance - 25°C (Typ)	-
Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Operating Temperature	-40°C ~ 85°C
Package / Case Radial, Disc Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Ratings	-
Size / Dimension 0.532" L x 0.236" W (13.50mm x 6.00mm) Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.496" (12.60mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing - 0.197" (5.00mm)	Size / Dimension	0.532" L x 0.236" W (13.50mm x 6.00mm)
Lead Spacing 0.197" (5.00mm)	Height - Seated (Max)	0.496" (12.60mm)
	Thickness (Max)	-
Report errors?	Lead Spacing	0.197" (5.00mm)
		Report errors?

MF-R015/600-B-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MF-R015/600-B-2 Payment Methods



















MF-R015/600-B-2 Shipping Methods













If you have any question about MF-R015/600-B-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com