

## MF-RX075/72-0 Information



For Reference Only

Part Number MF-RX075/72-0

Manufacturer Bourns Inc.

Category Circuit Protection
PTC Resettable Fuses

**Description** FUSE PTC RESETTABLE 0.75A HOLD

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MF-RX075/72-0 Specifications

Manufacturer Part Number         MF-RX075/72-0           Manufacturer         Bourns Inc.           Category         Circuit Protection           PTC Resettable Fuses           Package         Radial, Disc           Series         Multifuse?, MF-RX/72           Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (lh) (Max)         750mA           Current - Trip (lt)         1.5A           Time to Trip         6.3s           Resistance - Initial (Ri) (Min)         180 mOhms           Resistance - Post Trip (R1) (Max)         600 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Adial, Disc           Size / Dimension         0.409° Dia x 0.122" W (10.40mm x 3.10mm)           Height - Seated (Max)         0.630" (16.00mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)           Report errors?	*	
Category         Circuit Protection           Package         Radial, Disc           Series         Multifuse?, MF-RX/72           Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (Ih) (Max)         750mA           Current - Trip (It)         1.5A           Time to Trip         6.3s           Resistance - Initial (Ri) (Min)         180 mOhms           Resistance - Post Trip (R1) (Max)         600 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.409° Dia x 0.122° W (10.40mm x 3.10mm)           Height - Seated (Max)         0.630° (16.00mm)           Thickness (Max)         -           Lead Spacing         0.201° (5.10mm)	Manufacturer Part Number	MF-RX075/72-0
Package         Radial, Disc           Series         Multifuse?, MF-RX/72           Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (lh) (Max)         750mA           Current - Trip (It)         1.5A           Time to Trip         6.3s           Resistance - Initial (Ri) (Min)         180 mOhms           Resistance - Post Trip (R1) (Max)         600 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.409" Dia x 0.122" W (10.40mm x 3.10mm)           Height - Seated (Max)         0.630" (16.00mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Manufacturer	Bourns Inc.
Package         Radial, Disc           Series         Multifuse?, MF-RX/72           Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (Ih) (Max)         750mA           Current - Trip (It)         1.5A           Time to Trip         6.3s           Resistance - Initial (Ri) (Min)         180 mOhms           Resistance - Post Trip (R1) (Max)         600 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.409" Dia x 0.122" W (10.40mm x 3.10mm)           Height - Seated (Max)         0.630" (16.00mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Category	Circuit Protection
Series         Multifuse?, MF-RX/72           Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (Ih) (Max)         750mA           Current - Trip (It)         1.5A           Time to Trip         6.3s           Resistance - Initial (Ri) (Min)         180 mOhms           Resistance - Post Trip (R1) (Max)         600 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.409" Dia x 0.122" W (10.40mm x 3.10mm)           Height - Seated (Max)         0.630" (16.00mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)		PTC Resettable Fuses
Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (Ih) (Max)         750mA           Current - Trip (It)         1.5A           Time to Trip         6.3s           Resistance - Initial (Ri) (Min)         180 mOhms           Resistance - Post Trip (R1) (Max)         600 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.409" Dia x 0.122" W (10.40mm x 3.10mm)           Height - Seated (Max)         0.630" (16.00mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Package	Radial, Disc
Voltage - Max         72V           Current - Max         40A           Current - Hold (lh) (Max)         750mA           Current - Trip (It)         1.5A           Time to Trip         6.3s           Resistance - Initial (Ri) (Min)         180 mOhms           Resistance - Post Trip (R1) (Max)         600 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.409" Dia x 0.122" W (10.40mm x 3.10mm)           Height - Seated (Max)         0.630" (16.00mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Series	Multifuse?, MF-RX/72
Current - Max       40A         Current - Hold (Ih) (Max)       750mA         Current - Trip (It)       1.5A         Time to Trip       6.3s         Resistance - Initial (Ri) (Min)       180 mOhms         Resistance - Post Trip (R1) (Max)       600 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.409" Dia x 0.122" W (10.40mm x 3.10mm)         Height - Seated (Max)       0.630" (16.00mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Туре	Polymeric
Current - Hold (Ih) (Max)       750mA         Current - Trip (It)       1.5A         Time to Trip       6.3s         Resistance - Initial (Ri) (Min)       180 mOhms         Resistance - Post Trip (R1) (Max)       600 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.409" Dia x 0.122" W (10.40mm x 3.10mm)         Height - Seated (Max)       0.630" (16.00mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Voltage - Max	72V
Current - Trip (It)       1.5A         Time to Trip       6.3s         Resistance - Initial (Ri) (Min)       180 mOhms         Resistance - Post Trip (R1) (Max)       600 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.409" Dia x 0.122" W (10.40mm x 3.10mm)         Height - Seated (Max)       0.630" (16.00mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Current - Max	40A
Time to Trip       6.3s         Resistance - Initial (Ri) (Min)       180 mOhms         Resistance - Post Trip (R1) (Max)       600 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.409" Dia x 0.122" W (10.40mm x 3.10mm)         Height - Seated (Max)       0.630" (16.00mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Current - Hold (Ih) (Max)	750mA
Resistance - Initial (Ri) (Min)  Resistance - Post Trip (R1) (Max)  Resistance - 25°C (Typ)  Operating Temperature  -40°C ~ 85°C  Ratings  - Mounting Type  Through Hole  Package / Case  Radial, Disc  Size / Dimension  0.409" Dia x 0.122" W (10.40mm x 3.10mm)  Height - Seated (Max)  0.630" (16.00mm)  Thickness (Max)  Lead Spacing  0.201" (5.10mm)	Current - Trip (It)	1.5A
Resistance - Post Trip (R1) (Max)  Resistance - 25°C (Typ)  Operating Temperature  -40°C ~ 85°C  Ratings  - Mounting Type  Through Hole  Package / Case  Radial, Disc  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  600 mOhms  600 mOhms 600 mOhms  600 mOhms	Time to Trip	6.3s
Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.409" Dia x 0.122" W (10.40mm x 3.10mm)         Height - Seated (Max)       0.630" (16.00mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Resistance - Initial (Ri) (Min)	180 mOhms
Operating Temperature  Ratings  - Mounting Type  Through Hole  Package / Case  Radial, Disc  Size / Dimension  0.409" Dia x 0.122" W (10.40mm x 3.10mm)  Height - Seated (Max)  0.630" (16.00mm)  Thickness (Max)  Lead Spacing  0.201" (5.10mm)	Resistance - Post Trip (R1) (Max)	600 mOhms
Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.409" Dia x 0.122" W (10.40mm x 3.10mm)           Height - Seated (Max)         0.630" (16.00mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Resistance - 25°C (Typ)	-
Mounting Type  Package / Case  Radial, Disc  Size / Dimension  0.409" Dia x 0.122" W (10.40mm x 3.10mm)  Height - Seated (Max)  0.630" (16.00mm)  Thickness (Max)  Lead Spacing  0.201" (5.10mm)	Operating Temperature	-40°C ~ 85°C
Package / Case         Radial, Disc           Size / Dimension         0.409" Dia x 0.122" W (10.40mm x 3.10mm)           Height - Seated (Max)         0.630" (16.00mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Ratings	-
Size / Dimension       0.409" Dia x 0.122" W (10.40mm x 3.10mm)         Height - Seated (Max)       0.630" (16.00mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Mounting Type	Through Hole
Height - Seated (Max)       0.630" (16.00mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Package / Case	Radial, Disc
Thickness (Max)  Lead Spacing  - 0.201" (5.10mm)	Size / Dimension	0.409" Dia x 0.122" W (10.40mm x 3.10mm)
Lead Spacing 0.201" (5.10mm)	Height - Seated (Max)	0.630" (16.00mm)
	Thickness (Max)	-
Report errors?	Lead Spacing	0.201" (5.10mm)
		Report errors?

#### MF-RX075/72-0 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MF-RX075/72-0 Payment Methods



















## MF-RX075/72-0 Shipping Methods













If you have any question about MF-RX075/72-0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com