

### MF-RX160-005 Information



For Reference Only

Part Number MF-RX160-005

Manufacturer Bourns Inc.

Category Circuit Protection
PTC Resettable Fuses

**Description** FUSE PTC RESETTABLE

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MF-RX160-005 Specifications

Manufacturer Part Number         MF-RX160-005           Manufacturer         Bourns Inc.           Category         Circuit Protection           Package         Radial, Disc           Series         Multifuse?, MF-RX           Type         Polymeric           Voltage - Max         60V           Current - Max         40A           Current - Frip (It)         3.2A           Time to Trip         11.4s           Resistance - Initial (Ri) (Min)         90 mOhms           Resistance - Post Trip (R1) (Max)         220 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.642" L x 0.122" W (16.30mm x 3.10mm)           Height - Seated (Max)         0.839" (21.30mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)           Report errors?	1	
Category         Circuit Protection           Package         Radial, Disc           Series         Multifuse?, MF-RX           Type         Polymeric           Voltage - Max         60V           Current - Max         40A           Current - Hold (Ih) (Max)         1.6A           Current - Trip (It)         3.2A           Time to Trip         11.4s           Resistance - Initial (Ri) (Min)         90 mOhms           Resistance - Post Trip (R1) (Max)         220 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.642" L x 0.122" W (16.30mm x 3.10mm)           Height - Seated (Max)         0.839" (21.30mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Manufacturer Part Number	MF-RX160-005
Package         Radial, Disc           Series         Multifuse?, MF-RX           Type         Polymeric           Voltage - Max         60V           Current - Max         40A           Current - Hold (lh) (Max)         1.6A           Current - Trip (It)         3.2A           Time to Trip         11.4s           Resistance - Initial (Ri) (Min)         90 mOhms           Resistance - Post Trip (R1) (Max)         220 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.642" L x 0.122" W (16.30mm x 3.10mm)           Height - Seated (Max)         0.839" (21.30mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Manufacturer	Bourns Inc.
Package         Radial, Disc           Series         Multifuse?, MF-RX           Type         Polymeric           Voltage - Max         60V           Current - Max         40A           Current - Hold (Ih) (Max)         1.6A           Current - Trip (It)         3.2A           Time to Trip         11.4s           Resistance - Initial (Ri) (Min)         90 mOhms           Resistance - Post Trip (R1) (Max)         220 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.642" L x 0.122" W (16.30mm x 3.10mm)           Height - Seated (Max)         0.839" (21.30mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Category	Circuit Protection
Series         Multifuse?, MF-RX           Type         Polymeric           Voltage - Max         60V           Current - Max         40A           Current - Hold (Ih) (Max)         1.6A           Current - Trip (It)         3.2A           Time to Trip         11.4s           Resistance - Initial (Ri) (Min)         90 mOhms           Resistance - Post Trip (R1) (Max)         220 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.642" L x 0.122" W (16.30mm x 3.10mm)           Height - Seated (Max)         0.839" (21.30mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)		PTC Resettable Fuses
Type         Polymeric           Voltage - Max         60V           Current - Max         40A           Current - Hold (lh) (Max)         1.6A           Current - Trip (It)         3.2A           Time to Trip         11.4s           Resistance - Initial (Ri) (Min)         90 mOhms           Resistance - Post Trip (R1) (Max)         220 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.642" L x 0.122" W (16.30mm x 3.10mm)           Height - Seated (Max)         0.839" (21.30mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Package	Radial, Disc
Voltage - Max       60V         Current - Max       40A         Current - Hold (lh) (Max)       1.6A         Current - Trip (It)       3.2A         Time to Trip       11.4s         Resistance - Initial (Ri) (Min)       90 mOhms         Resistance - Post Trip (R1) (Max)       220 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.642" L x 0.122" W (16.30mm x 3.10mm)         Height - Seated (Max)       0.839" (21.30mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Series	Multifuse?, MF-RX
Current - Max       40A         Current - Hold (Ih) (Max)       1.6A         Current - Trip (It)       3.2A         Time to Trip       11.4s         Resistance - Initial (Ri) (Min)       90 mOhms         Resistance - Post Trip (R1) (Max)       220 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.642" L x 0.122" W (16.30mm x 3.10mm)         Height - Seated (Max)       0.839" (21.30mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Туре	Polymeric
Current - Hold (Ih) (Max)       1.6A         Current - Trip (It)       3.2A         Time to Trip       11.4s         Resistance - Initial (Ri) (Min)       90 mOhms         Resistance - Post Trip (R1) (Max)       220 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.642" L x 0.122" W (16.30mm x 3.10mm)         Height - Seated (Max)       0.839" (21.30mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Voltage - Max	60V
Current - Trip (It)       3.2A         Time to Trip       11.4s         Resistance - Initial (Ri) (Min)       90 mOhms         Resistance - Post Trip (R1) (Max)       220 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.642" L x 0.122" W (16.30mm x 3.10mm)         Height - Seated (Max)       0.839" (21.30mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Current - Max	40A
Time to Trip       11.4s         Resistance - Initial (Ri) (Min)       90 mOhms         Resistance - Post Trip (R1) (Max)       220 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.642" L x 0.122" W (16.30mm x 3.10mm)         Height - Seated (Max)       0.839" (21.30mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Current - Hold (Ih) (Max)	1.6A
Resistance - Initial (Ri) (Min)       90 mOhms         Resistance - Post Trip (R1) (Max)       220 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.642" L x 0.122" W (16.30mm x 3.10mm)         Height - Seated (Max)       0.839" (21.30mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Current - Trip (It)	3.2A
Resistance - Post Trip (R1) (Max)  Resistance - 25°C (Typ)  Operating Temperature  -40°C ~ 85°C  Ratings  - Mounting Type  Through Hole  Package / Case  Radial, Disc  Size / Dimension  0.642" L x 0.122" W (16.30mm x 3.10mm)  Height - Seated (Max)  0.839" (21.30mm)  Thickness (Max)  - Lead Spacing  0.201" (5.10mm)	Time to Trip	11.4s
Resistance - 25°C (Typ)       -         Operating Temperature       -40°C ~ 85°C         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.642" L x 0.122" W (16.30mm x 3.10mm)         Height - Seated (Max)       0.839" (21.30mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Resistance - Initial (Ri) (Min)	90 mOhms
Operating Temperature         -40°C ~ 85°C           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.642" L x 0.122" W (16.30mm x 3.10mm)           Height - Seated (Max)         0.839" (21.30mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Resistance - Post Trip (R1) (Max)	220 mOhms
Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.642" L x 0.122" W (16.30mm x 3.10mm)           Height - Seated (Max)         0.839" (21.30mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Resistance - 25°C (Typ)	-
Mounting Type  Package / Case  Radial, Disc  Size / Dimension  0.642" L x 0.122" W (16.30mm x 3.10mm)  Height - Seated (Max)  0.839" (21.30mm)  Thickness (Max)  Lead Spacing  0.201" (5.10mm)	Operating Temperature	-40°C ~ 85°C
Package / Case         Radial, Disc           Size / Dimension         0.642" L x 0.122" W (16.30mm x 3.10mm)           Height - Seated (Max)         0.839" (21.30mm)           Thickness (Max)         -           Lead Spacing         0.201" (5.10mm)	Ratings	-
Size / Dimension       0.642" L x 0.122" W (16.30mm x 3.10mm)         Height - Seated (Max)       0.839" (21.30mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Mounting Type	Through Hole
Height - Seated (Max)       0.839" (21.30mm)         Thickness (Max)       -         Lead Spacing       0.201" (5.10mm)	Package / Case	Radial, Disc
Thickness (Max)  Lead Spacing  0.201" (5.10mm)	Size / Dimension	0.642" L x 0.122" W (16.30mm x 3.10mm)
Lead Spacing 0.201" (5.10mm)	Height - Seated (Max)	0.839" (21.30mm)
	Thickness (Max)	-
Report errors?	Lead Spacing	0.201" (5.10mm)
		Report errors?

### MF-RX160-005 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MF-RX160-005 Payment Methods



















## MF-RX160-005 Shipping Methods













If you have any question about MF-RX160-005, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com