



### **MFA350PS24-STF Information**



For Reference Only

Part Number MFA350PS24-STF

Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 24V 350W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# MFA350PS24-STF Specifications

Manufacturer Part Number         MFA350PS24-STF           Manufacturer         XP Power           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MFA           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         14.5A           Power (Watts)         350W (361W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MFA           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         14.5A           Power (Watts)         350W (361W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Manufacturer Part Number	MFA350PS24-STF
Package         -           Series         MFA           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         14.5A           Power (Watts)         350W (361W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Manufacturer	XP Power
Package         -           Series         MFA           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         14.5A           Power (Watts)         350W (361W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         MFA           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         14.5A           Power (Watts)         350W (361W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         14.5A           Power (Watts)         350W (361W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         87%           Operating Temperature         -10°C ~ 70°C (With Derating)           Features         Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Package	-
Number of Outputs  1 Voltage - Input  85 ~ 264 VAC  Voltage - Output 1  24V  Voltage - Output 2  - Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  14.5A  Power (Watts)  350W (361W Forced Air)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  87%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type  Size / Dimension  6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Series	MFA
Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)14.5APower (Watts)350W (361W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Type	Enclosed
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Strice of Sor (With Derating)  Features  Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type  Size / Dimension  24V  24V  24V  24V  24V  24V  24V  24	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  Features  Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Output 4  - Current - Output (Max)  - 14.5A  - Current - Output (Max)  1TE (Commercial)  3kV (3000V)  87%  Operating Temperature  - 10°C ~ 70°C (With Derating)  Chassis Mount  6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Voltage - Output 1	24V
Voltage - Output 4  Current - Output (Max)  14.5A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  87%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  -0.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  87%  Operating Temperature  -10°C ~ 70°C (With Derating)  Features  Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  14.5A  14.5A  15.5A  16.50 W (361W Forced Air)  17.50 W (361W Forced Air)  18.50 W (3000V)  18.50 W	Voltage - Output 3	-
Power (Watts) 350W (361W Forced Air)  Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 87%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 87%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Current - Output (Max)	14.5A
Voltage - Isolation 3kV (3000V)  Efficiency 87%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Power (Watts)	350W (361W Forced Air)
Efficiency 87%  Operating Temperature -10°C ~ 70°C (With Derating)  Features Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Applications	ITE (Commercial)
Operating Temperature  -10°C ~ 70°C (With Derating)  Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Efficiency	87%
Mounting Type Chassis Mount Size / Dimension 6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Operating Temperature	-10°C ~ 70°C (With Derating)
Size / Dimension 6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)	Features	Adjustable Output, Hot Swappable, Load Sharing, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	6.80" L x 3.33" W x 2.80" H (172.7mm x 84.5mm x 52.8mm)
		Report errors?

#### **MFA350PS24-STF Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **MFA350PS24-STF Payment Methods**



















## MFA350PS24-STF Shipping Methods













If you have any question about MFA350PS24-STF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com