



MGN2CM-DC110 Information



For Reference Only

Part Number MGN2CM-DC110

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 30A 110V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MGN2CM-DC110 Specifications

Manufacturer Part Number MGN2CM-DC110 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MGN Relay Type General Purpose Coil Type Non Latching Coil Current 18.2mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 30A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMGNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.2mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)30ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeaturesInsulation - Class FMounting TypeChassis MountTermination StyleScrew Terminal	Manufacturer Part Number	MGN2CM-DC110
Package-SeriesMGNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.2mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)30ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeaturesInsulation - Class FMounting TypeChassis MountTermination StyleScrew Terminal	Manufacturer	Omron Automation and Safety
Package-SeriesMGNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.2mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)30ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeaturesInsulation - Class FMounting TypeChassis MountTermination StyleScrew Terminal	Category	Relays
SeriesMGNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.2mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)30ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeaturesInsulation - Class FMounting TypeChassis MountTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 18.2mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 30A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Release Time Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal	Package	-
Coil TypeNon LatchingCoil Current18.2mACoil Voltage110VDCContact FormDPDT (2 Form C)Contact Rating (Current)30ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)82.5 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeaturesInsulation - Class FMounting TypeChassis MountTermination StyleScrew Terminal	Series	MGN
Coil Current Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 30A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal	Relay Type	General Purpose
Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 30A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Release Time Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 30A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Current	18.2mA
Contact Rating (Current) Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Voltage	110VDC
Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 82.5 VDC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features Insulation - Class F Mounting Type Chassis Mount Termination Style 82.5 VDC	Contact Rating (Current)	30A
Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal	Switching Voltage	600VAC, 28VDC - Max
Operate Time30msRelease Time30msFeaturesInsulation - Class FMounting TypeChassis MountTermination StyleScrew Terminal	Turn On Voltage (Max)	82.5 VDC
Release Time 30ms Features Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal	Turn Off Voltage (Min)	-
Features Insulation - Class F Mounting Type Chassis Mount Termination Style Screw Terminal	Operate Time	30ms
Mounting Type Chassis Mount Termination Style Screw Terminal	Release Time	30ms
Termination Style Screw Terminal	Features	Insulation - Class F
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal
		Report errors?

MGN2CM-DC110 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MGN2CM-DC110 Payment Methods



















MGN2CM-DC110 Shipping Methods













If you have any question about MGN2CM-DC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com