

MI-251-MY-F1 Information

Heisener.com

Part Number MI-251-MY-F1 **Manufacturer** Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERT DC/DC 155VIN 12VOUT 50W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MI-251-MY-F1 Specifications

Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.16A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C		
Power Supplies - Board Mount	Manufacturer Part Number	MI-251-MY-F1
Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Output (Max) 210V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.16A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Manufacturer	Vicor Corporation
Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.16A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Category	Power Supplies - Board Mount
Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.16A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.16A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.16A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Series	MI-200
Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.16A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Туре	Isolated Module
Voltage - Input (Max) 210V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.16A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Number of Outputs	1
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.16A Power (Watts) 50W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Voltage - Input (Min)	100V
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Voltage - Input (Max)	210V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -55°C ~ 85°C	Voltage - Output 2	-
Current - Output (Max) $4.16A$ Power (Watts) $50W$ Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesRemote On/Off, OCP, OTP, OVPOperating Temperature $-55^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Output 3	-
Power (Watts) $50W$ Voltage - Isolation $3kV (3000V)$ Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature $-55^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Output 4	-
Voltage - Isolation $3kV (3000V)$ ApplicationsITE (Commercial)FeaturesRemote On/Off, OCP, OTP, OVPOperating Temperature $-55^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Current - Output (Max)	4.16A
Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature $-55^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Power (Watts)	50W
Features Remote On/Off, OCP, OTP, OVP Operating Temperature $-55^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Voltage - Isolation	3kV (3000V)
Operating Temperature $-55^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Applications	ITE (Commercial)
	Features	Remote On/Off, OCP, OTP, OVP
Efficiency 90%	Operating Temperature	-55°C ~ 85°C
Efficiency	Efficiency	90%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Full Brick	Package / Case	Full Brick
Size / Dimension 4.20" L x 2.40" W x 0.75" H (106.7mm x 61.0mm x 19.0mm)	Size / Dimension	4.20" L x 2.40" W x 0.75" H (106.7mm x 61.0mm x 19.0mm)

Supplier Device Package	-
Control Features	-
	Report errors?

MI-251-MY-F1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MI-251-MY-F1 Payment Methods



















MI-251-MY-F1 Shipping Methods













If you have any question about MI-251-MY-F1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com