

MI-25V-IW-F4 Information

Heisener.com

Part Number MI-25V-IW-F4 Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONV DC/DC 155VIN 5.8VOUT 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MI-25V-IW-F4 Specifications

Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick		
Category Power Supplies - Board Mount Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Manufacturer Part Number	
Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Manufacturer	Vicor Corporation
Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Category	Power Supplies - Board Mount
Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick		DC DC Converters
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Package	Full Brick
Number of Outputs 1 Voltage - Input (Min) 100V Voltage - Input (Max) 210V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Series	MI-200
Voltage - Input (Min) 100V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Туре	Isolated Module
Voltage - Input (Max) 210V Voltage - Output 1 5.8V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features Remote On/Off, OCP, OTP, OVP Operating Temperature Efficiency Mounting Type Through Hole Package / Case Full Brick	Voltage - Input (Min)	100V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features Remote On/Off, OCP, OTP, OVP Operating Temperature Efficiency Mounting Type Package / Case Poutput (Max) - Current - Output (Max) 17.2A 100W 100W	Voltage - Input (Max)	210V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature Efficiency Mounting Type Through Hole Package / Case Full Brick	Voltage - Output 1	5.8V
Voltage - Output 4 Current - Output (Max) 17.2A Power (Watts) 100W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 100W Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Voltage - Output 3	-
Power (Watts) Voltage - Isolation 3kV (3000V) Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Voltage - Output 4	-
Voltage - Isolation3kV (3000V)ApplicationsITE (Commercial)FeaturesRemote On/Off, OCP, OTP, OVPOperating Temperature-40°C ~ 85°CEfficiency90%Mounting TypeThrough HolePackage / CaseFull Brick	Current - Output (Max)	17.2A
Applications ITE (Commercial) Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Power (Watts)	100W
Features Remote On/Off, OCP, OTP, OVP Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Voltage - Isolation	3kV (3000V)
Operating Temperature -40°C ~ 85°C Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Applications	ITE (Commercial)
Efficiency 90% Mounting Type Through Hole Package / Case Full Brick	Features	Remote On/Off, OCP, OTP, OVP
Mounting Type Through Hole Package / Case Full Brick	Operating Temperature	-40°C ~ 85°C
Package / Case Full Brick	Efficiency	90%
	Mounting Type	Through Hole
Size / Dimension 4 20" L x 2 40" W x 1 00" H (106 7mm x 61 0mm x 25 4mm)	Package / Case	Full Brick
512c / Dimension 7.20 L x 2.40 W x 1.00 H (100./Hilli x 01.0Hilli x 23.4Hilli)	Size / Dimension	4.20" L x 2.40" W x 1.00" H (106.7mm x 61.0mm x 25.4mm)

Supplier Device Package	-
Control Features	-
	Report errors?

MI-25V-IW-F4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MI-25V-IW-F4 Payment Methods





















MI-25V-IW-F4 Shipping Methods













If you have any question about MI-25V-IW-F4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com