

MI-261-IX-F4 Information

Heisener.com

Part Number MI-261-IX-F4 Manufacturer Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERT DC/DC 270VIN 12VOUT 75W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MI-261-IX-F4 Specifications

Manufacturer Part Number Manufacturer Vicor Corporation Power Supplies - Board Mount DC DC Converters Package Full Brick Series MI-200 Type Isolated Module Number of Outputs I Voltage - Input (Min) Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Voltage - Isolation Applications MI-261-IX-F4 Vicor Corporation MI-261-IX-F4 Vicor Corporation Vicor Corporation 1 Vicor Corporation Vicor Corporation 1 Vicor Corporation 1 Vicor Corporation 1 Voltage Full Brick MI-200 1 I 200 I 25V Voltage - Input (Max) Voltage - Output 1 I 2V Voltage - Output 2 Voltage - Output 3 Voltage - Output 3 Voltage - Output (Max) For Woltage - Output (Max) ITE (Commercial)	
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Input (Max) 400V Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Output 4 - Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Current - Output (Max) 6.25A Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Power (Watts) 75W Voltage - Isolation 3kV (3000V)	
Voltage - Isolation 3kV (3000V)	
Applications ITE (Commercial)	
Features Remote On/Off, OCP, OTP, OVP	
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Efficiency 90%	
Mounting Type Through Hole	
Package / Case Full Brick	
Size / Dimension 4.20" L x 2.40" W x 1.00" H (106.7mm x 61.0mm x 25.4mm)	

Supplier Device Package	-
Control Features	-
	Report errors?

MI-261-IX-F4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MI-261-IX-F4 Payment Methods



















MI-261-IX-F4 Shipping Methods













If you have any question about MI-261-IX-F4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com