

MI-262-MX-F2 Information

Heisener.com

Part Number MI-262-MX-F2 **Manufacturer** Vicor Corporation

Category Power Supplies - Board Mount

DC DC Converters

Description CONVERT DC/DC 270VIN 15VOUT 75W

Package Full Brick

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MI-262-MX-F2 Specifications

Manufacturer Part Number Manufacturer Vicor Corporation Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) Voltage - Input (Max) Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Voltage - Isolation 3kV (3000V) Applications Features MI-262-MX-F2 Vicor Corporation NI-262-MX-F2 Voltage - Board Mount Voltage - William Voltage - William Voltage - Output 1 Series Vicor Corporation 1 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Features Remote On/Off, OCP, OTP, OVP
Category Power Supplies - Board Mount DC DC Converters Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Output (Max) 400V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Package Full Brick Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Series MI-200 Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Type Isolated Module Number of Outputs 1 Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Number of Outputs 1 Voltage - Input (Min) 125 V Voltage - Input (Max) 400 V Voltage - Output 1 15 V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75 W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Voltage - Input (Min) 125V Voltage - Input (Max) 400V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Voltage - Input (Max) 400V Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Voltage - Output 4 Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Current - Output (Max) 5A Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Power (Watts) 75W Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Voltage - Isolation 3kV (3000V) Applications ITE (Commercial)
Applications ITE (Commercial)
Features Remote On/Off, OCP, OTP, OVP
Operating Temperature $-55^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Efficiency 90%
Mounting Type Through Hole
Package / Case Full Brick
Size / Dimension 4.20" L x 2.40" W x 1.00" H (106.7mm x 61.0mm x 25.4mm)

Supplier Device Package	-
Control Features	-
	Report errors?

MI-262-MX-F2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MI-262-MX-F2 Payment Methods



















MI-262-MX-F2 Shipping Methods













If you have any question about MI-262-MX-F2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com