



#### **MIC4126YME Information**



For Reference Only

Part Number MIC4126YME

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

**Description**IC DRIVER MOSFET 1.5A DUAL 8SOIC**Package**8-SOIC (0.154", 3.90mm Width) Exposed Pad

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MIC4126YME Specifications**

Manufacturer Part NumberMIC4126YMEManufacturerMicrochip TechnologyCategoryIntegrated Circuits (ICs)PMIC - Gate DriversPackage8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)1.5A, 1.5AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 18nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP		
CategoryIntegrated Circuits (ICs)PMIC - Gate DriversPackage8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)1.5A, 1.5AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 18nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed Pad	Manufacturer Part Number	MIC4126YME
Package 8-SOIC (0.154", 3.90mm Width) Exposed Pad  Series - Driven Configuration Low-Side  Channel Type Independent  Number of Drivers 2 Gate Type N-Channel MOSFET  Voltage - Supply 4.5 V ~ 20 V  Logic Voltage - VIL, VIH 0.8V, 2.4V  Current - Peak Output (Source, Sink) 1.5A, 1.5A  Input Type Inverting  High Side Voltage - Max (Bootstrap) -  Rise / Fall Time (Typ) 20ns, 18ns  Operating Temperature -40°C ~ 125°C (TJ)  Mounting Type Surface Mount  Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad	Manufacturer	Microchip Technology
Package8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)1.5A, 1.5AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 18nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed Pad	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)1.5A, 1.5AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 18nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed Pad		PMIC - Gate Drivers
Driven Configuration  Channel Type  Independent  Number of Drivers  2  Gate Type  N-Channel MOSFET  Voltage - Supply  Logic Voltage - VIL, VIH  0.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad	Package	8-SOIC (0.154", 3.90mm Width) Exposed Pad
Channel Type Independent  Number of Drivers 2  Gate Type N-Channel MOSFET  Voltage - Supply 4.5 V ~ 20 V  Logic Voltage - VIL, VIH 0.8V, 2.4V  Current - Peak Output (Source, Sink) 1.5A, 1.5A  Input Type Inverting  High Side Voltage - Max (Bootstrap) -  Rise / Fall Time (Typ) 20ns, 18ns  Operating Temperature -40°C ~ 125°C (TJ)  Mounting Type Surface Mount  Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad	Series	-
Number of Drivers  Gate Type  N-Channel MOSFET  Voltage - Supply  4.5 V ~ 20 V  Logic Voltage - VIL, VIH  0.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  20ns, 18ns  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad	Driven Configuration	Low-Side
Gate TypeN-Channel MOSFETVoltage - Supply4.5 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)1.5A, 1.5AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 18nsOperating Temperature-40°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed Pad	Channel Type	Independent
Voltage - Supply  4.5 V ~ 20 V  Logic Voltage - VIL, VIH  0.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  20ns, 18ns  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad	Number of Drivers	2
Logic Voltage - VIL, VIH  Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad	Gate Type	N-Channel MOSFET
Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad	Voltage - Supply	4.5 V ~ 20 V
Input Type Inverting  High Side Voltage - Max (Bootstrap) -  Rise / Fall Time (Typ) 20ns, 18ns  Operating Temperature -40°C ~ 125°C (TJ)  Mounting Type Surface Mount  Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad	Logic Voltage - VIL, VIH	0.8V, 2.4V
High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  20ns, 18ns  Operating Temperature  -40°C ~ 125°C (TJ)  Mounting Type  Surface Mount  Package / Case  8-SOIC (0.154", 3.90mm Width) Exposed Pad	Current - Peak Output (Source, Sink)	1.5A, 1.5A
Rise / Fall Time (Typ) 20ns, 18ns Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad	Input Type	Inverting
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C} \text{ (TJ)}$ Mounting Type Surface Mount  Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad	High Side Voltage - Max (Bootstrap)	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad	Rise / Fall Time (Typ)	20ns, 18ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad	Operating Temperature	-40°C ~ 125°C (TJ)
-	Mounting Type	Surface Mount
Supplier Device Package 8-SOIC-EP	Package / Case	8-SOIC (0.154", 3.90mm Width) Exposed Pad
	Supplier Device Package	8-SOIC-EP
Report errors?		Report errors?

#### **MIC4126YME Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **MIC4126YME Payment Methods**





















## **MIC4126YME Shipping Methods**













If you have any question about MIC4126YME, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com