



MIC4423YM-TR Information



For Reference Only

Part Number MIC4423YM-TR

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

Description IC DRIVER MOSFET 3A DUAL 8-SOIC

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MIC4423YM-TR Specifications

Manufacturer Part Number MIC4423YM-TR Manufacturer Microchip Technology Category Integrated Circuits (ICs) PACKAGE 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) 3A, 3A Input Type Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 28ns, 32ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC		
CategoryIntegrated Circuits (ICs)PMIC - Gate DriversPackage8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)3A, 3AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)28ns, 32nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Manufacturer Part Number	MIC4423YM-TR
Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) 3A, 3A Input Type Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 28ns, 32ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer	Microchip Technology
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)3A, 3AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)28ns, 32nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)3A, 3AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)28ns, 32nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC		PMIC - Gate Drivers
Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)3A, 3AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)28ns, 32nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Package	8-SOIC (0.154", 3.90mm Width)
Channel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)3A, 3AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)28ns, 32nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Series	-
Number of Drivers Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Driven Configuration	Low-Side
Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 28ns, 32ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Independent
Voltage - Supply Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Gate Type	N-Channel, P-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Voltage - Supply	4.5 V ~ 18 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Logic Voltage - VIL, VIH	0.8V, 2.4V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 28ns, 32ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Current - Peak Output (Source, Sink)	3A, 3A
Rise / Fall Time (Typ) 28ns, 32ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Input Type	Inverting
Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	High Side Voltage - Max (Bootstrap)	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Rise / Fall Time (Typ)	28ns, 32ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Operating Temperature	-40°C ~ 150°C (TJ)
Supplier Device Package 8-SOIC	Mounting Type	Surface Mount
••	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors?

MIC4423YM-TR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MIC4423YM-TR Payment Methods



















MIC4423YM-TR Shipping Methods













If you have any question about MIC4423YM-TR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com