



### **MIC4423YN Information**

wy net ener com

For Reference Only

Part Number MIC4423YN

Manufacturer Microchip Technology

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

**Description** IC DRIVER MOSFET 3A DUAL 8DIP

**Package** 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MIC4423YN Specifications**

Manufacturer Part NumberMIC4423YNManufacturerMicrochip TechnologyCategoryIntegrated Circuits (ICs)PMIC - Gate DriversPackage8-DIP (0.300", 7.62mm)Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)3A, 3AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)28ns, 32nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-PDIP		
Category         Integrated Circuits (ICs)           PMIC - Gate Drivers           Package         8-DIP (0.300", 7.62mm)           Series         -           Driven Configuration         Low-Side           Channel Type         Independent           Number of Drivers         2           Gate Type         N-Channel, P-Channel MOSFET           Voltage - Supply         4.5 V ~ 18 V           Logic Voltage - VIL, VIH         0.8V, 2.4V           Current - Peak Output (Source, Sink)         3A, 3A           Input Type         Inverting           High Side Voltage - Max (Bootstrap)         -           Rise / Fall Time (Typ)         28ns, 32ns           Operating Temperature         -40°C ~ 150°C (TJ)           Mounting Type         Through Hole           Package / Case         8-DIP (0.300", 7.62mm)           Supplier Device Package         8-PDIP	Manufacturer Part Number	MIC4423YN
Package 8-DIP (0.300", 7.62mm)  Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) 3A, 3A Input Type Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 28ns, 32ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Manufacturer	Microchip Technology
Package8-DIP (0.300", 7.62mm)Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 18 VLogic Voltage - VIL, VIH0.8V, 2.4VCurrent - Peak Output (Source, Sink)3A, 3AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)28ns, 32nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-PDIP	Category	Integrated Circuits (ICs)
Series - Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) 3A, 3A Input Type Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 28ns, 32ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package		PMIC - Gate Drivers
Driven Configuration  Channel Type  Independent  Number of Drivers  2  Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  Logic Voltage - VIL, VIH  Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Package	8-DIP (0.300", 7.62mm)
Channel Type Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 18 V Logic Voltage - VIL, VIH 0.8V, 2.4V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 28ns, 32ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Series	-
Number of Drivers  Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  4.5 V ~ 18 V  Logic Voltage - VIL, VIH  0.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  28ns, 32ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Driven Configuration	Low-Side
Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  4.5 V ~ 18 V  Logic Voltage - VIL, VIH  0.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  28ns, 32ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Channel Type	Independent
Voltage - Supply  Logic Voltage - VIL, VIH  0.8V, 2.4V  Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  28ns, 32ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH  Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Gate Type	N-Channel, P-Channel MOSFET
Current - Peak Output (Source, Sink)  Input Type  Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Voltage - Supply	4.5 V ~ 18 V
Input Type  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Logic Voltage - VIL, VIH	0.8V, 2.4V
High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  28ns, 32ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Current - Peak Output (Source, Sink)	3A, 3A
Rise / Fall Time (Typ)  28ns, 32ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Input Type	Inverting
Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package  8-PDIP	High Side Voltage - Max (Bootstrap)	-
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Rise / Fall Time (Typ)	28ns, 32ns
Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Operating Temperature	-40°C ~ 150°C (TJ)
Supplier Device Package 8-PDIP	Mounting Type	Through Hole
	Package / Case	8-DIP (0.300", 7.62mm)
Report errors?	Supplier Device Package	8-PDIP
		Report errors?

### **MIC4423YN Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **MIC4423YN Payment Methods**



















### **MIC4423YN Shipping Methods**













If you have any question about MIC4423YN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com