



MIC5366-2.7YMT-TZ Information



For Reference Only

Part Number MIC5366-2.7YMT-TZ
Manufacturer Microchip Technology
Category Integrated Circuits (ICs)

PMIC - Voltage Regulators - Linear

Description IC REG LINEAR 2.7V 150MA 4TMLF **Package** 4-UDFN Exposed Pad, 4-TMLF?

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MIC5366-2.7YMT-TZ Specifications

Manufacturer Part Number Microchip Technology Category Integrated Circuits (ICs) Package 4-UDFN Exposed Pad, 4-TMLF? Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5 V Voltage - Output (Min/Fixed) 2.7 V Voltage - Output (Max) - Voltage - Output (Max) - Voltage - Output (Max) 0.38 V @ 150mA Current - Output 150mA Current - Supply (Max) 39μA PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Enable Protection Features Over Current, Over Temperature Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)		
Category Integrated Circuits (ICs) PMIC - Voltage Regulators - Linear Package 4-UDFN Exposed Pad, 4-TMLF? Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 2.7V Voltage - Output (Max) - Voltage Dropout (Max) 0.38V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 39µA PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Enable Protection Features Over Current, Over Temperature Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Manufacturer Part Number	MIC5366-2.7YMT-TZ
PMIC - Voltage Regulators - Linear Package 4-UDFN Exposed Pad, 4-TMLF? Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 2.7V Voltage - Output (Max) - Voltage Dropout (Max) 0.38V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 39μA PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Over Current, Over Temperature Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Manufacturer	Microchip Technology
Package 4-UDFN Exposed Pad, 4-TMLF? Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5 V Voltage - Output (Min/Fixed) 2.7 V Voltage - Output (Max) - Voltage Dropout (Max) 0.38 V @ 150 mA Current - Output 150 mA Current - Quiescent (Iq) - Current - Supply (Max) 39 μA PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Over Current, Over Temperature Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Category	Integrated Circuits (ICs)
Series - Output Configuration Positive Output Type Fixed Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 2.7V Voltage - Output (Max) - Voltage Dropout (Max) 0.38V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 39μA PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Enable Protection Features Over Current, Over Temperature Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)		PMIC - Voltage Regulators - Linear
Output ConfigurationPositiveOutput TypeFixedNumber of Regulators1Voltage - Input (Max)5.5VVoltage - Output (Min/Fixed)2.7VVoltage - Output (Max)-Voltage Dropout (Max)0.38V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)39µAPSRR80dB ~ 65dB (1kHz ~ 10kHz)Control FeaturesEnableProtection FeaturesOver Current, Over TemperatureOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case4-UDFN Exposed Pad, 4-TMLF?Supplier Device Package4-TMLF? (1x1)	Package	4-UDFN Exposed Pad, 4-TMLF?
Output Type Number of Regulators 1 Voltage - Input (Max) 5.5V Voltage - Output (Min/Fixed) 2.7V Voltage - Output (Max) - Voltage Dropout (Max) 0.38V @ 150mA Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) 93µA PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Protection Features Over Current, Over Temperature Operating Temperature Operating Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package	Series	-
Number of Regulators1Voltage - Input (Max)5.5VVoltage - Output (Min/Fixed)2.7VVoltage - Output (Max)-Voltage Dropout (Max)0.38V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)39μAPSRR80dB ~ 65dB (1kHz ~ 10kHz)Control FeaturesEnableProtection FeaturesOver Current, Over TemperatureOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case4-UDFN Exposed Pad, 4-TMLF?Supplier Device Package4-TMLF? (1x1)	Output Configuration	Positive
Voltage - Input (Max)5.5VVoltage - Output (Min/Fixed)2.7VVoltage - Output (Max)-Voltage Dropout (Max)0.38V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)39μAPSRR80dB ~ 65dB (1kHz ~ 10kHz)Control FeaturesEnableProtection FeaturesOver Current, Over TemperatureOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case4-UDFN Exposed Pad, 4-TMLF?Supplier Device Package4-TMLF? (1x1)	Output Type	Fixed
Voltage - Output (Min/Fixed)2.7VVoltage - Output (Max)-Voltage Dropout (Max)0.38V @ 150mACurrent - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)39μAPSRR80dB ~ 65dB (1kHz ~ 10kHz)Control FeaturesEnableProtection FeaturesOver Current, Over TemperatureOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case4-UDFN Exposed Pad, 4-TMLF?Supplier Device Package4-TMLF? (1x1)	Number of Regulators	1
Voltage - Output (Max) Voltage Dropout (Max) Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Enable Protection Features Operating Temperature Operating Temperature Aυ°C ~ 125°C Mounting Type Surface Mount Package / Case Supplier Device Package 4-TMLF? (1x1)	Voltage - Input (Max)	5.5V
Voltage Dropout (Max) Current - Output 150mA Current - Quiescent (Iq) - Current - Supply (Max) PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Enable Protection Features Operating Temperature Operating Type Surface Mount Package / Case Supplier Device Package 4-TMLF? (1x1)	Voltage - Output (Min/Fixed)	2.7V
Current - Output150mACurrent - Quiescent (Iq)-Current - Supply (Max)39μAPSRR80dB ~ 65dB (1kHz ~ 10kHz)Control FeaturesEnableProtection FeaturesOver Current, Over TemperatureOperating Temperature-40°C ~ 125°CMounting TypeSurface MountPackage / Case4-UDFN Exposed Pad, 4-TMLF?Supplier Device Package4-TMLF? (1x1)	Voltage - Output (Max)	-
Current - Quiescent (Iq) Current - Supply (Max) PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Enable Protection Features Over Current, Over Temperature Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Voltage Dropout (Max)	0.38V @ 150mA
Current - Supply (Max) PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Enable Protection Features Over Current, Over Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Current - Output	150mA
PSRR 80dB ~ 65dB (1kHz ~ 10kHz) Control Features Enable Protection Features Over Current, Over Temperature Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Current - Quiescent (Iq)	-
Control Features Protection Features Over Current, Over Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Current - Supply (Max)	39μΑ
Protection Features Over Current, Over Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	PSRR	80dB ~ 65dB (1kHz ~ 10kHz)
Operating Temperature -40°C ~ 125°C Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Control Features	Enable
Mounting Type Surface Mount Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Protection Features	Over Current, Over Temperature
Package / Case 4-UDFN Exposed Pad, 4-TMLF? Supplier Device Package 4-TMLF? (1x1)	Operating Temperature	-40°C ~ 125°C
Supplier Device Package 4-TMLF? (1x1)	Mounting Type	Surface Mount
. , ,	Package / Case	4-UDFN Exposed Pad, 4-TMLF?
Report errors?	Supplier Device Package	4-TMLF? (1x1)
		Report errors?

MIC5366-2.7YMT-TZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MIC5366-2.7YMT-TZ Payment Methods



















MIC5366-2.7YMT-TZ Shipping Methods













If you have any question about MIC5366-2.7YMT-TZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com