

**MILS1812-392K Information**


For Reference Only

**Part Number** [MILS1812-392K](#)  
**Manufacturer** API Delevan Inc.  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** FIXED IND 3.9UH 487MA 840 MOHM  
**Package** Nonstandard  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**MILS1812-392K Specifications**

Manufacturer Part Number	<a href="#">MILS1812-392K</a>
Manufacturer	API Delevan Inc.
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	Nonstandard
Series	MILS1812
Type	-
Material - Core	Ferrite
Inductance	3.9μH
Tolerance	±10%
Current Rating	487mA
Current - Saturation	-
Shielding	Shielded
DC Resistance (DCR)	840 mOhm Max
Q @ Freq	40 @ 7.9MHz
Frequency - Self Resonant	56MHz
Ratings	-
Operating Temperature	-55°C ~ 125°C
Frequency - Test	7.9MHz
Features	-
Mounting Type	Surface Mount
Package / Case	Nonstandard
Supplier Device Package	-
Size / Dimension	0.190" L x 0.134" W (4.83mm x 3.40mm)

Height - Seated (Max)	0.134" (3.40mm)
<a href="#">Report errors?</a>	

## MILS1812-392K Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MILS1812-392K Payment Methods



## MILS1812-392K Shipping Methods



If you have any question about MILS1812-392K, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)