

**MILS1812R-822K Information**


For Reference Only

**Part Number** [MILS1812R-822K](#)  
**Manufacturer** API Delevan Inc.  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** FIXED IND 8.2UH 372MA 1.44 OHM  
**Package** Nonstandard  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**MILS1812R-822K Specifications**

Manufacturer Part Number	<a href="#">MILS1812R-822K</a>
Manufacturer	API Delevan Inc.
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	Nonstandard
Series	MILS1812R
Type	-
Material - Core	Ferrite
Inductance	8.2μH
Tolerance	±10%
Current Rating	372mA
Current - Saturation	-
Shielding	Shielded
DC Resistance (DCR)	1.44 Ohm Max
Q @ Freq	40 @ 7.9MHz
Frequency - Self Resonant	30MHz
Ratings	-
Operating Temperature	-55°C ~ 125°C
Frequency - Test	7.9MHz
Features	-
Mounting Type	Surface Mount
Package / Case	Nonstandard
Supplier Device Package	-
Size / Dimension	0.190" L x 0.134" W (4.83mm x 3.40mm)

Height - Seated (Max)

0.134" (3.40mm)

[Report errors?](#)

## MILS1812R-822K Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MILS1812R-822K Payment Methods



## MILS1812R-822K Shipping Methods



If you have any question about MILS1812R-822K, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)