



## **MJN1C-I-DC24 Information**



For Reference Only

Part Number MJN1C-I-DC24

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MJN1C-I-DC24 Specifications**

Manufacturer Part Number     MJNIC-I-DC24       Manufacturer     Omron Automation and Safety       Category     Relays       Power Relays, Over 2 Amps       Package     -       Series     MJN       Relay Type     General Purpose       Coil Type     Non Latching       Coil Current     50mA       Coil Voltage     24VDC       Contact Form     SPDT (1 Form C)       Contact Rating (Current)     10A       Switching Voltage     600VAC, 28VDC - Max       Turn On Voltage (Max)     18 VDC       Turn Off Voltage (Min)     -       Operate Time     20ms       Release Time     10ms       Features     Test Button       Mounting Type     Socketable       Termination Style     Plug In, Quick Connect - 0.187" (4.7mm)		
Category Relays Power Relays, Over 2 Amps  Package - Series MJN Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	MJN1C-I-DC24
Package-SeriesMJNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current50mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Manufacturer	Omron Automation and Safety
Package-SeriesMJNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current50mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesMJNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current50mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 50mA  Coil Voltage 24VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 10A  Switching Voltage 600VAC, 28VDC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) -  Operate Time 20ms  Release Time 10ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Package	-
Coil TypeNon LatchingCoil Current50mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Series	MJN
Coil Current50mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  10A  Switching Voltage 600VAC, 28VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min) - Operate Time 20ms  Release Time 10ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Current	50mA
Contact Rating (Current)  Switching Voltage  600VAC, 28VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  20ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.187" (4.7mm)	Coil Voltage	24VDC
Switching Voltage 600VAC, 28VDC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) - Operate Time 20ms  Release Time 10ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  20ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.187" (4.7mm)	Switching Voltage	600VAC, 28VDC - Max
Operate Time 20ms  Release Time 10ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	18 VDC
Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	-
Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Operate Time	20ms
Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Release Time	10ms
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Features	Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
Tepor virous		Report errors?

#### **MJN1C-I-DC24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **MJN1C-I-DC24 Payment Methods**





















## **MJN1C-I-DC24 Shipping Methods**













If you have any question about MJN1C-I-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com