



MJN3C-I-DC125 Information



For Reference Only

Part Number MJN3C-I-DC125

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 10A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MJN3C-I-DC125 Specifications

| Manufacturer Part NumberMJN3C-I-DC125ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMJNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage125VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)93.75 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm) | | |
|--|--------------------------|---|
| CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMJNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage125VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)93.75 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm) | Manufacturer Part Number | MJN3C-I-DC125 |
| Package - Series MJN Relay Type General Purpose Coil Type Non Latching Coil Current 9.6mA Coil Voltage 125VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 93.75 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Manufacturer | Omron Automation and Safety |
| Package-SeriesMJNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage125 VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage600 VAC, 28 VDC - MaxTurn On Voltage (Max)93.75 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm) | Category | Relays |
| SeriesMJNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage125 VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage600 VAC, 28 VDC - MaxTurn On Voltage (Max)93.75 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm) | | Power Relays, Over 2 Amps |
| Relay Type General Purpose Coil Type Non Latching Coil Current 9.6mA Coil Voltage 125 VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 600 VAC, 28 VDC - Max Turn On Voltage (Max) 93.75 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Package | - |
| Coil TypeNon LatchingCoil Current9.6mACoil Voltage125VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)93.75 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm) | Series | MJN |
| Coil Current9.6mACoil Voltage125VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage600VAC, 28VDC - MaxTurn On Voltage (Max)93.75 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm) | Relay Type | General Purpose |
| Coil Voltage 125VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 93.75 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Coil Type | Non Latching |
| Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 93.75 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Coil Current | 9.6mA |
| Contact Rating (Current) Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 93.75 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Coil Voltage | 125VDC |
| Switching Voltage 600VAC, 28VDC - Max Turn On Voltage (Max) 93.75 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Contact Form | 3PDT (3 Form C) |
| Turn On Voltage (Max) 7 | Contact Rating (Current) | 10A |
| Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Switching Voltage | 600VAC, 28VDC - Max |
| Operate Time 20ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Turn On Voltage (Max) | 93.75 VDC |
| Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Turn Off Voltage (Min) | - |
| Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Operate Time | 20ms |
| Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Release Time | 10ms |
| Termination Style Plug In, Quick Connect - 0.187" (4.7mm) | Features | Test Button |
| | Mounting Type | Socketable |
| | Termination Style | Plug In, Quick Connect - 0.187" (4.7mm) |
| Report errors? | | Report errors? |

MJN3C-I-DC125 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MJN3C-I-DC125 Payment Methods





















MJN3C-I-DC125 Shipping Methods













If you have any question about MJN3C-I-DC125, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com