



MK2KP AC120 Information

Heisener.com

Part Number MK2KP AC120

Manufacturer Omron Automation and Safety

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 120V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MK2KP AC120 Specifications

Manufacturer Part NumberMK2KP AC120ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current19mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeSocketable		
Category Relays Power Relays, Over 2 Amps Package - Series MKK Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 19mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features -	Manufacturer Part Number	MK2KP AC120
Package - Series MKK Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 19mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features -	Manufacturer	Omron Automation and Safety
Package - Series MKK Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 19mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features -	Category	Relays
SeriesMKKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current19mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 19mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features -	Package	-
Coil Type Latching, Dual Coil Coil Current 19mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features -	Series	MKK
Coil Current19mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features -	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features -	Coil Current	19mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) Features 5A 250VAC, 250VDC - Max 96 VAC 30ms 30ms 30ms Features	Coil Voltage	120VAC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) - Operate Time 30ms Release Time 30ms Features -	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Features 96 VAC	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time Release Time 30ms Features -	Switching Voltage	250VAC, 250VDC - Max
Operate Time 30ms Release Time 30ms Features -	Turn On Voltage (Max)	96 VAC
Release Time 30ms Features -	Turn Off Voltage (Min)	-
Features -	Operate Time	30ms
	Release Time	30ms
Mounting Type Socketable	Features	-
	Mounting Type	Socketable
Termination Style Plug In, 11 Pin (Octal)	Termination Style	Plug In, 11 Pin (Octal)
Report errors?		Report errors?

MK2KP AC120 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MK2KP AC120 Payment Methods





















MK2KP AC120 Shipping Methods













If you have any question about MK2KP AC120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com