

MK2KP DC125

est a Quote

MK2KP DC125 Information

Part Number	MK2KP DC125	
Manufacturer	Omron Automation and Safety	
Category	Relays Power Relays, Over 2 Amps	
Description Package	RELAY GEN PURPOSE DPDT 5A 125V	
	-	
	For the pricing/inventory/lead time, please contact	
	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	
	Manufacturer Category Description	Power Relays, Over 2 Amps Description RELAY GEN PURPOSE DPDT 5A 125V Package - For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MK2KP DC125 Specifications

ManufacturerOmron Automation and SafetyCategoryRelaysPackage-Package-SeriesMKKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current21.6mAColid VoltageDPDT (2 Form C)Contact Form5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operat Time30msRelease Time-Features-Munting TypeSocketableTermination StylePurp (n) (Cutal)		
CategoryRelaysPackage-Package-SeriesMKKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current21.6mACoil Voltage125VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelase Time-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer Part Number	MK2KP DC125
PackagePower Relays, Over 2 AmpsPackage-SeriesMKKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current21.6mACoil Voltage125VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer	Omron Automation and Safety
Package-SeriesMKKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current21.6mACoil Voltage125VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Category	Relays
SeriesMKKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current21.6mACoil Voltage125 VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250 VAC, 250 VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StyleHug In, 11 Pin (Octal)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeRelay TypeLatching, Dual CoilCoil TypeLatching, Dual CoilCoil Current21.6mACoil Voltage125VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage (Max)100 VDC - MaxTurn On Voltage (Max).Operate Time30msRelease Time.Features.Features.Mounting TypeDieg (Max)Termination StylePurg (Deta)	Package	-
Coil TypeLatching, Dual CoilCoil Current21.6mACoil Voltage125VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time-Features-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Series	МКК
Coil Current21.6mACoil Voltage125VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Relay Type	General Purpose
Coil Voltage125VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelease Times30msFeatures-Mounting TypeSocketableTermination StyleHug In, 11 Pin (Octal)	Coil Type	Latching, Dual Coil
Contact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Coil Current	21.6mA
Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Coil Voltage	125VDC
Switching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)100 VDCTurn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Contact Rating (Current)	5A
Turn Off Voltage (Min)-Operate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Switching Voltage	250VAC, 250VDC - Max
Operate Time30msRelease Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Turn On Voltage (Max)	100 VDC
Release Time30msFeatures-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Turn Off Voltage (Min)	-
Features-Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Operate Time	30ms
Mounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Release Time	30ms
Termination Style Plug In, 11 Pin (Octal)	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 11 Pin (Octal)
		Report errors?

MK2KP DC125 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MK2KP DC125 Payment Methods



MK2KP DC125 Shipping Methods



If you have any question about MK2KP DC125, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com