

MK2P-I-AC220 Information

Heisener.com

Part Number MK2P-I-AC220

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 220V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MK2P-I-AC220 Specifications

Manufacturer Part Number MK2P-I-AC220 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Manufacturer Part Number	MK2P-I-AC220
Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Purpose MK MK General Purpose General Purpose DMA Seneral Purpose 11mA Coil Voltage 11mA 20VAC 250VAC 250VDC - Max 250VDC - Max 250VAC 250VDC - Max 250VAC 250VDC - Max 250VAC 250VDC - Max	Manufacturer	Omron Automation and Safety
Package-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Category	Relays
SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Package	-
Coil TypeNon LatchingCoil Current11mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Series	MK
Coil Current Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 220VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Relatures Mechanical Indicator Mounting Type Socketable Termination Style	Coil Current	11mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Coil Voltage	220VAC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Switching Voltage	250VAC, 250VDC - Max
Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Turn On Voltage (Max)	176 VAC
Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Turn Off Voltage (Min)	66 VAC
Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Release Time	20ms
Termination Style Plug In, 8 Pin (Octal)	Features	Mechanical Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 8 Pin (Octal)
		Report errors?

MK2P-I-AC220 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MK2P-I-AC220 Payment Methods



















MK2P-I-AC220 Shipping Methods













If you have any question about MK2P-I-AC220, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com