



MK2PD-S-DC12 Information

Heisener.com

Part Number MK2PD-S-DC12

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 12V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MK2PD-S-DC12 Specifications

Manufacturer Part Number MK2PD-S-DC12 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 126mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current126mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time30msRelease Time20msFeaturesDiode, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Manufacturer Part Number	MK2PD-S-DC12
Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 126mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Purpose	Manufacturer	Omron Automation and Safety
Package - MK Relay Type General Purpose Coil Type Non Latching Coil Current 126mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Category	Relays
SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current126mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time30msRelease Time20msFeaturesDiode, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 126mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Package	-
Coil TypeNon LatchingCoil Current126mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time30msRelease Time20msFeaturesDiode, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 8 Pin (Octal)	Series	MK
Coil Current Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Coil Current	126mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Coil Voltage	12VDC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 1.8 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Switching Voltage	250VAC, 250VDC - Max
Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Turn On Voltage (Max)	9.6 VDC
Release Time 20ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Turn Off Voltage (Min)	1.8 VDC
Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Operate Time	30ms
Mounting Type Socketable Termination Style Plug In, 8 Pin (Octal)	Release Time	20ms
Termination Style Plug In, 8 Pin (Octal)	Features	Diode, Mechanical Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 8 Pin (Octal)
		Report errors?

MK2PD-S-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MK2PD-S-DC12 Payment Methods



















MK2PD-S-DC12 Shipping Methods













If you have any question about MK2PD-S-DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com