



MK3P5-I-AC100 Information

Heisener.com

Part Number MK3P5-I-AC100

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 10A 100V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MK3P5-I-AC100 Specifications

Manufacturer Part Number MK3P5-I-AC100 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 27mA Coil Voltage 100VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)		
Category Relays Power Relays, Over 2 Amps Package	Manufacturer Part Number	MK3P5-I-AC100
Package-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current27mACoil Voltage100VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer	Omron Automation and Safety
Package-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current27mACoil Voltage100VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Category	Relays
SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current27mACoil Voltage100VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 27mA Coil Voltage 100VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Package	-
Coil TypeNon LatchingCoil Current27mACoil Voltage100VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Series	MK
Coil Current Coil Voltage 100VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 100VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Current	27mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Voltage	100VAC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style 80 VAC 20ms Analysis Anal	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Switching Voltage	250VAC, 250VDC - Max
Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn On Voltage (Max)	80 VAC
Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn Off Voltage (Min)	30 VAC
Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Release Time	20ms
Termination Style Plug In, 11 Pin (Octal)	Features	Mechanical Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 11 Pin (Octal)
		Report errors?

MK3P5-I-AC100 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MK3P5-I-AC100 Payment Methods





















MK3P5-I-AC100 Shipping Methods













If you have any question about MK3P5-I-AC100, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com