



MK3P5-I DC125 Information

Heisener.com

Part Number MK3P5-I DC125

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 10A 125V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MK3P5-I DC125 Specifications

Manufacturer Part NumberMK3P5-I DC125ManufacturerOmron Automation and SafetyCategoryRelaysPackage-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage125 VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250 VAC, 250 VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)18.75 VDCOperate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage125VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)18.75 VDCOperate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer Part Number	MK3P5-I DC125
Package-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage125VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)18.75 VDCOperate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer	Omron Automation and Safety
Package - MK Relay Type General Purpose Coil Type Non Latching Coil Current 12mA Coil Voltage 125VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 18.75 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Category	Relays
SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12mACoil Voltage125 VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250 VAC, 250 VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)18.75 VDCOperate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 12mA Coil Voltage 125VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 18.75 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Package	-
Coil TypeNon LatchingCoil Current12mACoil Voltage125VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)100 VDCTurn Off Voltage (Min)18.75 VDCOperate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Series	MK
Coil Current Coil Voltage 125VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 18.75 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 125VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 18.75 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 18.75 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Current	12mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 18.75 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Voltage	125VDC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 18.75 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) 100 VDC Turn Off Voltage (Min) 18.75 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Switching Voltage	250VAC, 250VDC - Max
Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn On Voltage (Max)	100 VDC
Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn Off Voltage (Min)	18.75 VDC
Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Operate Time	30ms
Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Release Time	20ms
Termination Style Plug In, 11 Pin (Octal)	Features	Mechanical Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 11 Pin (Octal)
		Report errors?

MK3P5-I DC125 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MK3P5-I DC125 Payment Methods



















MK3P5-I DC125 Shipping Methods













If you have any question about MK3P5-I DC125, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com