



## MK3PD-5-I-DC6 Information

Heisener.com

Part Number MK3PD-5-I-DC6

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 10A 6V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MK3PD-5-I-DC6 Specifications**

Manufacturer Part Number  Manufacturer  Omron Automation and Safety  Relays  Power Relays, Over 2 Amps  Package		
CategoryRelaysPackage-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current255mACoil Voltage6VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.9 VDCOperate Time30msRelease Time20msFeaturesDiode, Mechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer Part Number	MK3PD-5-I-DC6
Package-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current255mACoil Voltage6VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.9 VDCOperate Time30msRelease Time20msFeaturesDiode, Mechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer	Omron Automation and Safety
Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 255mA Coil Voltage 6VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Category	Relays
SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current255mACoil Voltage6VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.9 VDCOperate Time30msRelease Time20msFeaturesDiode, Mechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 255mA Coil Voltage 6VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Package	-
Coil Type Coil Current 255mA Coil Voltage 6VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator Mounting Type Socketable Termination Style Non Latching 105 Non C 106 Non C 107 Non C 108 109 109 100 100 100 100 100 100 100 100	Series	MK
Coil Current255mACoil Voltage6VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.9 VDCOperate Time30msRelease Time20msFeaturesDiode, Mechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 30ms Release Time 20ms Features Diode, Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 4.8 VDC  Turn Off Voltage (Min) 0.9 VDC  Operate Time 30ms  Release Time 20ms  Features Diode, Mechanical Indicator  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Coil Current	255mA
Contact Rating (Current)  Switching Voltage  250VAC, 250VDC - Max  Turn On Voltage (Max)  4.8 VDC  Turn Off Voltage (Min)  0.9 VDC  Operate Time  30ms  Release Time  20ms  Features  Diode, Mechanical Indicator  Mounting Type  Socketable  Termination Style  Plug In, 11 Pin (Octal)	Coil Voltage	6VDC
Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 4.8 VDC  Turn Off Voltage (Min) 0.9 VDC  Operate Time 30ms  Release Time 20ms  Features Diode, Mechanical Indicator  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  30ms  Release Time  20ms  Features  Diode, Mechanical Indicator  Mounting Type  Socketable  Termination Style  Plug In, 11 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  30ms  Release Time  20ms  Features  Diode, Mechanical Indicator  Mounting Type  Socketable  Termination Style  Plug In, 11 Pin (Octal)	Switching Voltage	250VAC, 250VDC - Max
Operate Time 30ms  Release Time 20ms  Features Diode, Mechanical Indicator  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Turn On Voltage (Max)	4.8 VDC
Release Time 20ms  Features Diode, Mechanical Indicator  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Turn Off Voltage (Min)	0.9 VDC
Features Diode, Mechanical Indicator  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Operate Time	30ms
Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Release Time	20ms
Termination Style Plug In, 11 Pin (Octal)	Features	Diode, Mechanical Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 11 Pin (Octal)
		Report errors?

#### MK3PD-5-I-DC6 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### MK3PD-5-I-DC6 Payment Methods



















### **MK3PD-5-I-DC6 Shipping Methods**













If you have any question about MK3PD-5-I-DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com