



MK3PN-5-S-DC110 Information

Heisener.com

Part Number MK3PN-5-S-DC110

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 10A 110V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MK3PN-5-S-DC110 Specifications

Manufacturer Part Number MK3PN-5-S-DC110 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 15.1mA Coil Voltage 110VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)		
Category Relays Power Relays, Over 2 Amps Package - Series MK Relay Type General Purpose Coil Type Non Latching Coil Current 15.1mA Coil Voltage 110VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Fermination Style Pug In, 11 Pin (Octal)	Manufacturer Part Number	MK3PN-5-S-DC110
Package-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.1mACoil Voltage110VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer	Omron Automation and Safety
Package-SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.1mACoil Voltage110VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Category	Relays
SeriesMKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.1mACoil Voltage110VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 15.1mA Coil Voltage 110VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Package	-
Coil TypeNon LatchingCoil Current15.1mACoil Voltage110VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Series	MK
Coil Current15.1mACoil Voltage110VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 110VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Current	15.1mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Voltage	110VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Switching Voltage	250VAC, 250VDC - Max
Operate Time 30ms Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn On Voltage (Max)	88 VDC
Release Time 20ms Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn Off Voltage (Min)	16.5 VDC
Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Operate Time	30ms
Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Release Time	20ms
Termination Style Plug In, 11 Pin (Octal)	Features	LED Indicator, Mechanical Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 11 Pin (Octal)
		Report errors?

MK3PN-5-S-DC110 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MK3PN-5-S-DC110 Payment Methods





















MK3PN-5-S-DC110 Shipping Methods













If you have any question about MK3PN-5-S-DC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com