



MKJ3A6F9-19PN Information



For Reference Only

Part Number MKJ3A6F9-19PN **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 19POS STRGHT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKJ3A6F9-19PN Specifications

Manufacturer Part Number MKJ3A6F9-19PN Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-38999, MKJ3 Connector Type Plug, Male Pins Number of Positions 19 Shell Size - Insert 9-19 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999, MKJ3Connector TypePlug, Male PinsNumber of Positions19Shell Size - Insert9-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Manufacturer Part Number	MKJ3A6F9-19PN
Package-SeriesMIL-DTL-38999, MKJ3Connector TypePlug, Male PinsNumber of Positions19Shell Size - Insert9-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-38999, MKJ3Connector TypePlug, Male PinsNumber of Positions19Shell Size - Insert9-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Category	Connectors, Interconnects
SeriesMIL-DTL-38999, MKJ3Connector TypePlug, Male PinsNumber of Positions19Shell Size - Insert9-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions19Shell Size - Insert9-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Package	-
Number of Positions19Shell Size - Insert9-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Series	MIL-DTL-38999, MKJ3
Shell Size - Insert9-19Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Features Shielded Voltage - Rated 500VAC Current Rating 5 Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Crimp Free Hanging (In-Line) Free Hanging (In-Line	Number of Positions	19
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Shell Size - Insert	9-19
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Gold Cold Shielded Shielded Shielded Shielded Shielded Shielded	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Material, Finish	Aluminum Alloy, Nickel Plated, Electroless
Voltage - Rated 500VAC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
	Voltage - Rated	500VAC
Report errors?	Current Rating	5A
		Report errors?

MKJ3A6F9-19PN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKJ3A6F9-19PN Payment Methods



















MKJ3A6F9-19PN Shipping Methods













If you have any question about MKJ3A6F9-19PN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com