



MKJ3A7F6-4SN Information



For Reference Only

Part NumberMKJ3A7F6-4SNManufacturerITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 4POS JAM NUT W/SKTS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKJ3A7F6-4SN Specifications

Manufacturer Part Number MKJ3A7F6-4SN Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-38999, MKJ3 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A		
Category Circular Connectors Circular Connectors Package - Series MIL-DTL-38999, MKJ3 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated Voltage - Rated Current Rating 5 MIL-DTL-38999, MKJ3 - Connector MIL-DTL-38999, MKJ3 Aluminum Sockets MIL-DTL-38999, MKJ3 - Contact Finish Gol4 Sockets - Contact Finish Gold Sockets - Contact Finish Gold Sockets Shielded Voltage - Rated SoovAC Current Rating	Manufacturer Part Number	MKJ3A7F6-4SN
Circular Connectors Package - Series MIL-DTL-38999, MKJ3 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-38999, MKJ3Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert6-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Category	Connectors, Interconnects
SeriesMIL-DTL-38999, MKJ3Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert6-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert6-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Package	-
Number of Positions Shell Size - Insert 6-4 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Series	MIL-DTL-38999, MKJ3
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Number of Positions	4
Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Shell Size - Insert	6-4
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Shell Material, Finish Gold Current Rating Aluminum Alloy, Nickel Plated, Electroless Gold Shielded Shielded 500VAC	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Material, Finish	Aluminum Alloy, Nickel Plated, Electroless
Voltage - Rated 500VAC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
	Voltage - Rated	500VAC
D	Current Rating	5A
Report errors?		Report errors?

MKJ3A7F6-4SN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKJ3A7F6-4SN Payment Methods



















MKJ3A7F6-4SN Shipping Methods













If you have any question about MKJ3A7F6-4SN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com