



MKJ3B7W10-26SN Information



For Reference Only

Part Number MKJ3B7W10-26SN Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 26POS JAM NUT W/SKTS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKJ3B7W10-26SN Specifications

Manufacturer Part Number MKJ3B7W10-26SN Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-38999, MKJ3 Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 10-26 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999, MKJ3 Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 10-26 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Manufacturer Part Number	MKJ3B7W10-26SN
Package-SeriesMIL-DTL-38999, MKJ3Connector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert10-26Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-38999, MKJ3 Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 10-26 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Category	Connectors, Interconnects
Series MIL-DTL-38999, MKJ3 Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 10-26 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert10-26Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Package	-
Number of Positions Shell Size - Insert 10-26 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Series	MIL-DTL-38999, MKJ3
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shielded Voltage - Rated 500VAC Current Rating 5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Number of Positions	26
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Size - Insert	10-26
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Gold Shielded Shielded 500VAC	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
-	Voltage - Rated	500VAC
Report errors?	Current Rating	5A
		Report errors?

MKJ3B7W10-26SN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKJ3B7W10-26SN Payment Methods



















MKJ3B7W10-26SN Shipping Methods













If you have any question about MKJ3B7W10-26SN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com