



MKJ4A1F6-4S Information



For Reference Only

Part Number MKJ4A1F6-4S Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 4POS STRGHT W/SKTS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKJ4A1F6-4S Specifications

Manufacturer Part Number MKJ4A1F6-4S Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-38999, MKJ4 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 6-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Push-Pull Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999, MKJ4Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert6-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Manufacturer Part Number	MKJ4A1F6-4S
Circular ConnectorsPackage-SeriesMIL-DTL-38999, MKJ4Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert6-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-38999, MKJ4Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert6-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Category	Connectors, Interconnects
SeriesMIL-DTL-38999, MKJ4Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert6-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert6-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Package	-
Number of Positions Shell Size - Insert 6-4 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Push-Pull Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Series	MIL-DTL-38999, MKJ4
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Push-Pull Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Features Shielded Voltage - Rated Current Rating 6-4 6-4 6-4 6-4 6-4 6-4 6-4 6-	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Push-Pull Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 5A	Number of Positions	4
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated500VACCurrent Rating5A	Shell Size - Insert	6-4
Termination Crimp Fastening Type Push-Pull Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating Aluminum Alloy, Nickel Plated, Electroless Gold Shielded Shielded 500VAC	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 500VAC Current Rating 5A	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 500VAC Current Rating 5A	Shell Material, Finish	Aluminum Alloy, Nickel Plated, Electroless
Voltage - Rated 500VAC Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Shielded
	Voltage - Rated	500VAC
Report errors?	Current Rating	5A
		Report errors?

MKJ4A1F6-4S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKJ4A1F6-4S Payment Methods



















MKJ4A1F6-4S Shipping Methods













If you have any question about MKJ4A1F6-4S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com