

MKP1837368015

Request a Quote

MKP1837368015 Information

Contraction territory	Part Number	MKP1837368015
	Manufacturer	Vishay BC Components
	Category	Capacitors Film Capacitors
	Description	CAP FILM 0.068UF 10% 160VDC RAD
	Package	Radial
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP1837368015 Specifications

Manufacturer Part NumberMKP1837368015ManufacturerVishay BC ComponentsCategoryCapacitorsPackageFilm CapacitorsPackageRadialSeriesMKP1837Capacitance0.068µFTolerance±10%Voltage Rating - AC100VVoltage Rating - DC160VDielectric Material>100yropylene (PP), MetallizedSerkage / Case-Munufing Type55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSiz / Dimension0.354" (9.00mm)Height - Seated (Max)0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingPartners-Lead Spacing1.97" (5.00mm)Applications-Martners-Requences-Requences-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-Martners-		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP1837Capacitance0.068µFTolerance±10%Voltage Rating - AC100VVoltage Rating - DC160VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing.0197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	MKP1837368015
Film CapacitorsPackageRadialSeriesMKP1837Capacitance0.068µFTolerance±10%Voltage Rating - AC100VVoltage Rating - DC160VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP1837Capacitance0.068µFTolerance±10%Voltage Rating - AC100VVoltage Rating - DC160VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)Lead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
SeriesMKP1837Capacitance0.068µFTolerance±10%Voltage Rating - AC100VVoltage Rating - DC60VDielectric MaterialPolypropylenc (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 100°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.295" k r 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)Lead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-		Film Capacitors
Capacitance0.068µFTolerance±10%Voltage Rating - AC100VVoltage Rating - DC60VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 100°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)Lead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package	Radial
Tolerance±10%Yoltage Rating - AC100VVoltage Rating - DC160VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	MKP1837
Voltage Rating - AC100VVoltage Rating - DC160VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	0.068µF
Voltage Rating - DC160VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	$\pm 10\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	100V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	160V
Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.295" L x 0.295" W (7.50mm x 7.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	-55°C ~ 100°C
Size / Dimension 0.295" L x 0.295" W (7.50mm x 7.50mm) Height - Seated (Max) 0.354" (9.00mm) Termination PC Pins Lead Spacing 0.197" (5.00mm) Applications High Frequency, Switching Features -	Mounting Type	Through Hole
Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	0.295" L x 0.295" W (7.50mm x 7.50mm)
Lead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	0.354" (9.00mm)
ApplicationsHigh Frequency, SwitchingFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.197" (5.00mm)
	Applications	High Frequency, Switching
Papart array	Features	-
Keport errors		Report errors?

MKP1837368015 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP1837368015 Payment Methods



MKP1837368015 Shipping Methods



If you have any question about MKP1837368015, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com