

# MKP1840315634

quest a Quote

### MKP1840315634 Information

Heisener.com	Part Number	MKP1840315634
	Manufacturer	Vishay BC Components
	Category	Capacitors Film Capacitors
	Description	CAP FILM 0.015UF 5% RADIAL
	Package	Radial
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# MKP1840315634 Specifications

Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-		
Category   Capacitors     Film Capacitors   Film Capacitors     Package   Radial     Series   MKP1840     Capacitance   0.015µF     Tolerance   0.015µF     Voltage Rating - AC   -     Voltage Rating - DC   -     Dielectric Material   Polypropylene (PP), Metallized     Operating Temperature   -     Operating Type   Through Hole     Package / Case   Radial     Size / Dimension   0.394" (10.00mm)     Height - Seated (Max)   0.394" (10.00mm)     Applications   DC Link, DC Filtering; High Pulse, DV/DT     Features   -	Manufacturer Part Number	MKP1840315634
Film CapacitorsPackageRadialSeriesMKP1840Capacitance0.015µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)Per Pins0.394" (10.00mm)Applications0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP1840Capacitance0.015µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)ApplicationsOC lins, DC Link, DC Filtering; High Pulse, DV/DTFeatures-	Category	Capacitors
Series   MKP1840     Capacitance   0.015µF     Tolerance   ±5%     Voltage Rating - AC   -     Voltage Rating - DC   -     Dielectric Material   Polypropylene (PP), Metallized     Dielectric Material   -     Operating Temperature   -     Mounting Type   -     Package / Case   Radial     Size / Dimension   0.9492" L x 0.158" W (12.50mm x 4.00mm)     Height - Seated (Max)   0.394" (10.00mm)     Lead Spacing   0.394" (10.00mm)     Applications   DC Link, DC Filtering; High Pulse, DV/DT     Features   -		Film Capacitors
Capacitance0.015µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.394" (10.00mm)Height - Seated (Max)0.394" (10.00mm)Lead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" (10.00mm) x 4.00mm)Height - Seated (Max)O.394" (10.00mm)Lead Spacing0.394" (10.00mm)Lead SpacingDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Series	MKP1840
NotifiedDescriptionVoltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Capacitance	0.015μF
Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Voltage Rating - DC	-
Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Operating Temperature	$-55^{\circ}C \sim 100^{\circ}C$
Size / Dimension 0.492" L x 0.158" W (12.50mm x 4.00mm)   Height - Seated (Max) 0.394" (10.00mm)   Termination PC Pins   Lead Spacing 0.394" (10.00mm)   Applications DC Link, DC Filtering; High Pulse, DV/DT   Features -	Mounting Type	Through Hole
Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Size / Dimension	0.492" L x 0.158" W (12.50mm x 4.00mm)
Lead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.394" (10.00mm)
ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.394" (10.00mm)
	Applications	DC Link, DC Filtering; High Pulse, DV/DT
Report errors?	Features	-
Report criois:		Report errors?

#### MKP1840315634 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MKP1840315634 Payment Methods



## MKP1840315634 Shipping Methods



If you have any question about MKP1840315634, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com