

# MKP1840368014

Request a Quote

#### MKP1840368014 Information

Heisener.com	Part Number	MKP1840368014
	Manufacturer	Vishay BC Components
	Category	Capacitors Film Capacitors
	Description	CAP FILM 0.068UF 5% RADIAL
	Package	Radial
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### MKP1840368014 Specifications

New Part of the sector of th		
Category Capacitors   Film Capacitors Film Capacitors   Package Radial   Series Radial   Capacitance 0.068µF   Tolerance ±5%   Voltage Rating - AC -   Voltage Rating - DC -   Dielectric Material Polypropylene (PP), Metallized   Operating Temperature -   Voltage / Case Radial   Size / Dimension 0.283" L x 0.177" W (7.20mm x 4.50mm)   Height - Seated (Max) 0.354" (9.00mm)   Termination PC Pins   Lead Spacing 0.197" (5.00mm)   Applications DC Link, DC Filtering; High Pulse, DV/DT   Features -	Manufacturer Part Number	MKP1840368014
Film CapacitorsPackageRadialSeriesMKP1840Capacitance0.068µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283° L x 0.177° W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197° (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP1840Capacitance0.068µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolyproylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)Lead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP1840   Capacitance 0.068µF   Tolerance ±5%   Voltage Rating - AC -   Voltage Rating - DC -   Dielectric Material Polypropylene (PP), Metallized   DSR (Equivalent Series Resistance) -   Operating Temperature -55°C ~ 100°C   Mounting Type Through Hole   Package / Case Radial   Size / Dimension 0.253" L x 0.177" W (7.20mm x 4.50mm)   Height - Seated (Max) 0.354" (9.00mm)   Lead Spacing 0.197" (5.00mm)   Applications DC Link, DC Filtering; High Pulse, DV/DT   Features -		Film Capacitors
Capacitance0.068µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)O.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Series	MKP1840
NoticitiesEnvironmentVoltage Rating - AC-Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Capacitance	0.068µF
Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFettures-	Tolerance	±5%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Voltage Rating - DC	-
Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Operating Temperature	$-55^{\circ}$ C ~ $100^{\circ}$ C
Size / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Size / Dimension	0.283" L x 0.177" W (7.20mm x 4.50mm)
Lead Spacing0.197" (5.00mm)ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.354" (9.00mm)
ApplicationsDC Link, DC Filtering; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.197" (5.00mm)
	Applications	DC Link, DC Filtering; High Pulse, DV/DT
Report errors?	Features	-
Report chois.		Report errors?

#### MKP1840368014 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MKP1840368014 Payment Methods



#### MKP1840368014 Shipping Methods



If you have any question about MKP1840368014, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com