

MKP1848C67580JY5

MKP1848C67580JY5 Information



| Part Number | MKP1848C67580JY5 | |
|--------------|--|--|
| Manufacturer | Vishay BC Components | |
| Category | Capacitors Film Capacitors | |
| Description | CAP FILM 75UF 5% 800VDC RAD 4LD | |
| Package | Radial - 4 Leads | |
| | For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com | |
| | | |
| | E-mail: salesdept@heisener.com | |



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP1848C67580JY5 Specifications

| Manufacturer Part NumberMKP1848C67580JY5ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRadial - 4 LeadsSeriesMKP1848CCapacitance75µFTolerance±5%Voltage Rating - AC800VDielectric Material90yproylene (PP), MetallizedDielectric Material55°C ~ 105°CMounting Type55°C ~ 105°CMounting Type2264" L x 1.772" W (57.50mm x 45.00mm)Field Maxon772" (45.00mm)Height - Seated (Maxon)ColorsLead Spacing2067" (52.50mm)Lead Spacing2.067" (52.50mm)Lead SpacingColorsLead SpacingColors< | | |
|---|------------------------------------|---|
| CategoryCapacitorsFilm CapacitorsPackageRadial - 4 LeadsSeriesMKP1848CCapacitance75µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material3 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Manufacturer Part Number | MKP1848C67580JY5 |
| Him CapacitorsPackageRadial - 4 LeadsSeriesMKP1848CCapacitance75µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)3 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Manufacturer | Vishay BC Components |
| PackageRadial - 4 LeadsSeriesMKP1848CCapacitance75µFTolerance±5%Voltage Rating - AC800VVoltage Rating - DC90yropylene (PP), MetallizedDielectric Material90yropylene (PP), MetallizedSSR (Equivalent Series Resistance)3mOhmOperating Temperature-55°C ~ 105°CMounting TypeRadial - 4 LeadsSize / Dimension2.64" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)FerminationDC PinsLead Spacing0.60"" (52.50mm)ApplicationsDC Link, DC Filtering | Category | Capacitors |
| SeriesMKP1848CCapacitance75µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material3 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)Lead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | | Film Capacitors |
| Capacitance75µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material3mOhmOperating Temperature55°C ~ 105°CMounting TypeHrough HolePackage / CaseRadial - 4 LeadsSize / Dimension1.72" (45.00mm x 45.00mm)Height - Seated (Max)9C PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Package | Radial - 4 Leads |
| Tolerance±5%Yoltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)3 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Series | MKP1848C |
| NoticeInterferenceVoltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)3 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Capacitance | 75µF |
| Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)3 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Tolerance | ±5% |
| Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material3 mOhmESR (Equivalent Series Resistance)3 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Voltage Rating - AC | - |
| ESR (Equivalent Series Resistance)3 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Voltage Rating - DC | 800V |
| Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Dielectric Material | Polypropylene (PP), Metallized |
| Nounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | ESR (Equivalent Series Resistance) | 3 mOhm |
| Package / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.772" W (57.50mm x 45.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Operating Temperature | -55°C ~ 105°C |
| Size / Dimension 2.264" L x 1.772" W (57.50mm x 45.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications DC Link, DC Filtering | Mounting Type | Through Hole |
| Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Package / Case | Radial - 4 Leads |
| TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Size / Dimension | 2.264" L x 1.772" W (57.50mm x 45.00mm) |
| Lead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering | Height - Seated (Max) | 1.772" (45.00mm) |
| Applications DC Link, DC Filtering | Termination | PC Pins |
| | Lead Spacing | 2.067" (52.50mm) |
| | Applications | DC Link, DC Filtering |
| Features Low ESR; Low ESL; Long Life | Features | Low ESR; Low ESL; Long Life |
| Report errors? | | Report errors? |

MKP1848C67580JY5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP1848C67580JY5 Payment Methods



If you have any question about MKP1848C67580JY5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com