


MKP383191063JDM2B0

MKP383191063JDM2B0 Information

Heisener.com	 MKP383191063JDM2B0 Vishay BC Components Capacitors Film Capacitors CAP FILM 910PF 5% 630VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP383191063JDM2B0 Specifications

ManufacturerVishay BC ComponentsCapacitorsFalm CapacitorsPackageRadialSeriesMMKP383Capacitance910pFTolerance±5%Voltage Rating - DC220VVoltage Rating - DC630VDielectric Material-Operating Temperature-55°C ~ 105°CVoltage J. CaseRadialSize / Dimension0.492° L x 0.158° W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)Applications0.394" (10.00mm)Applications0.394" (10.00mm)		
CategoryCapacitorsPackageRadialPackageRadialSeriesMMKP383Capacitance910pFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolyproylene (PP), MetallizedSeries Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension0.492° L x 0.158° W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	MKP383191063JDM2B0
Film CapacitorsPackageRadialSeriesMMKP383Capacitance910pFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMMKP383Capacitance910pFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)Lead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
Series MMKP383 Capacitance 910pF Tolerance ±5% Voltage Rating - AC 220V Voltage Rating - DC 630V Dielectric Material Polypropylene (PP), Metallized DSR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.394" (10.00mm) Height - Seated (Max) 0.394" (10.00mm) Applications General Purpose Features -		Film Capacitors
Capacitance910pFTolerance±5%Voltage Rating - AC20VVoltage Rating - DC630VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)Lead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" (10.00mm)Height - Seated (Max)0.394" (10.00mm)Lead Spacing0.394" (10.00mm)Lead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Series	MMKP383
Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Capacitance	910pF
Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	220V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	630V
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	$-55^{\circ}C \sim 105^{\circ}C$
Size / Dimension 0.492" L x 0.158" W (12.50mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Mounting Type	Through Hole
Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.492" L x 0.158" W (12.50mm x 4.00mm)
Lead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.394" (10.00mm)
Applications General Purpose Features -	Termination	PC Pins
Features -	Lead Spacing	0.394" (10.00mm)
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

MKP383191063JDM2B0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP383191063JDM2B0 Payment Methods



MKP383191063JDM2B0 Shipping Methods



If you have any question about MKP383191063JDM2B0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com