


MKP383311140JC02Z0

MKP383311140JC02Z0 Information

Heisener.com	Part Number Manufacturer Category Description Package		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP383311140JC02Z0 Specifications

ManufacturerVishay BC ComponentsCategoryCapacitorsFilm CapacitorsPackageRadialSeriesMMKP383Capacitance0.011µFTolerance±5%Voltage Rating - DC5000Voltage Rating - DC1400V (1.4kV)Dielectric Material-Operating Temperature-Operating Type-55°C ~ 105°CMounting Type560° (1.00mm) x 8.50mm)Package / Case6.689° L x 0.335° W (1.50mm x 8.50mm)Height - Seated (Max)0.669° (1.700mm)TerminationPC PinsLead Spacing0.295° (7.50mm)ApplicationsGeneral PurposeFeatures-Seatures-Seatures-Seatures-Starter Space-Starter Space- </th <th></th> <th></th>		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMMKP383Capacitance0.011µFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1400V (1.4kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMouning TypeThrough HolePackage / CaseRadialSize / Dimension0.669" (1.20mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	MKP383311140JC02Z0
Film CapacitorsPackageRadialSeriesMMKP383Capacitance0.011µFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1400V (1.4kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689° L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.669° (17.00mm)TerminationPC PinsLead Spacing0.295° (7.50mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMMKP383Capacitance0.011µFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1400V (1.4kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.669" (17.00mm) x 8.50mm)Height - Seated (Max)0.669" (17.00mm)Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
NumberMMKP383Capacitance0.011µFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1400V (1.4kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.669" (17.00mm) x 8.50mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-		Film Capacitors
Capacitance0.011µFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1400V (1.4kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.669" (17.00mm) x 8.50mm)Height - Seated (Max)0.669" (17.00mm)Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC500VVoltage Rating - DC1400V (1.4kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.669" (17.00mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Series	MMKP383
Voltage Rating - AC500VVoltage Rating - DC1400V (1.4kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.011µF
Voltage Rating - DC1400V (1.4kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	500V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	1400V (1.4kV)
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.669" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 105°C
Size / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.669" (17.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.689" L x 0.335" W (17.50mm x 8.50mm)
Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.669" (17.00mm)
Applications General Purpose Features -	Termination	PC Pins
Features -	Lead Spacing	0.295" (7.50mm)
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

MKP383311140JC02Z0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP383311140JC02Z0 Payment Methods



MKP383311140JC02Z0 Shipping Methods



If you have any question about MKP383311140JC02Z0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com