

MKP383327040JD02W0

MKP383327040JD02W0 Information

Heisener.com	Part Number	MKP383327040JD02W0	
	Manufacturer	Vishay BC Components	
	Category	Capacitors Film Capacitors	
	Description	CAP FILM 0.027UF 5% 400VDC RAD	
	Package	Radial	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

MKP383327040JD02W0 Specifications

ManufacturerVishay BC ComponentsCapacitorsFilm CapacitorsPackageRadialSeriesMMKP383Capacitance0.027µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropelne (PP), MetallizedDoprating Temperature-5°C ~ 105°CNounting TypeRadialSize / Dimension4049″ L x 0.197″ W (12.50mm x 5.00mm)Height - Seated (Max)0.949″ (10.00mm)TerminationC PinsLead Spacing6.941″ (10.00mm)Features6.941″ IntropenetFeatures6.941″ Intropenet		
Category Capacitors Film Capacitors Package Radial Series MMKP383 Capacitance 0.027μF Tolerance ±5% Voltage Rating - AC 200V Voltage Rating - DC 400V Dielectric Material Polyproplene (PP), Metallized SPR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Size / Dimension 0.492" L x 0.197" W (12.50mm x 5.00mm) Height - Seated (Max) 0.493" (11.00mm) Termination PC Pins Lead Spacing . Applications General Purpose Features .	Manufacturer Part Number	MKP383327040JD02W0
Fin CapacitorsPackageRadialSeriesMMKP383Capacitance0.027µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMMKP383Capacitance0.027μFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
Series MMKP383 Capacitance 0.027μF Tolerance ±5% Voltage Rating - AC 200V Voltage Rating - DC 400V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.433" (11.00mm) Height - Seated (Max) 0.394" (10.00mm) Applications General Purpose Features -		Film Capacitors
Capacitance0.027µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral Purpose	Package	Radial
Tolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Series	MMKP383
Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.027µF
Voltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	200V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	400V
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 105°C
Size / Dimension 0.492" L x 0.197" W (12.50mm x 5.00mm) Height - Seated (Max) 0.433" (11.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Mounting Type	Through Hole
Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.492" L x 0.197" W (12.50mm x 5.00mm)
Lead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.433" (11.00mm)
Applications General Purpose Features -	Termination	PC Pins
Features -	Lead Spacing	0.394" (10.00mm)
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

MKP383327040JD02W0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP383327040JD02W0 Payment Methods





If you have any question about MKP383327040JD02W0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com