

# MKP383339040JC02R0

### MKP383339040JC02R0 Information

| Heisener.com       | MKP383339040JC02R0<br>Vishay BC Components<br>Capacitors<br>Film Capacitors<br>CAP FILM 0.039UF 5% 400VDC RAD<br>Radial<br>For the pricing/inventory/lead time, please contact |                 |
|--------------------|--|-----------------|
| For Reference Only | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com  | Request a Quote |

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### MKP383339040JC02R0 Specifications

| ManufacturerVishay BC ComponentsCapacitorsFalm CapacitorsPackageRadialSeriesMMKP383Capacitance0.039µFTolerance±5%Voltage Rating - DC200VVoltage Rating - DC90yproylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CVoltage / CaseRadialSiz / Dimension0.492° L x 0.236° W (12.50mm x 6.00mm)Height - Seated (Max)0.51° (14.00mm)TerminationPC PinsApplications0.295° (7.50mm)Applications0.295° (7.50mm)  |                                    |  |
|---|------------------------------------|--|
| CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMMKP383Capacitance0.039µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMouting TypeThrough HolePackage / CaseRadialSize / Dimension0.492° L x 0.236° W (12.50mm x 6.00mm)Height - Seated (Max)0.551° (14.00mm)TerminationPC PinsLead Spacing0.295° (7.50mm)ApplicationsGeneral PurposeFeatures- | Manufacturer Part Number           | MKP383339040JC02R0                     |
| Film CapacitorsPackageRadialSeriesMMKP383Capacitance0.039µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-                  | Manufacturer                       | Vishay BC Components                   |
| PackageRadialSeriesMMKP383Capacitance0.039µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationQ295" (7.50mm)ApplicationsGeneral PurposeFeatures-  | Category                           | Capacitors                             |
| YearMMKP383Capacitance0.039µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.551" (14.00mm) x 6.00mm)Height - Seated (Max)0.251" (14.00mm)Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-  |                                    | Film Capacitors                        |
| Capacitance0.039μFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRatialPackage / CaseRadialSize / Dimension0.551" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-   | Package                            | Radial                                 |
| Tolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-   | Series                             | MMKP383                                |
| Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-  | Capacitance                        | 0.039µF                                |
| Voltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-  | Tolerance                          | ±5%                                    |
| Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-   | Voltage Rating - AC                | 200V                                   |
| ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-  | Voltage Rating - DC                | 400V                                   |
| Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-   | Dielectric Material                | Polypropylene (PP), Metallized         |
| Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-   | ESR (Equivalent Series Resistance) | -                                      |
| Package / CaseRadialSize / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-  | Operating Temperature              | -55°C ~ 105°C                          |
| Size / Dimension0.492" L x 0.236" W (12.50mm x 6.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-  | Mounting Type                      | Through Hole                           |
| Height - Seated (Max)0.551" (14.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-  | Package / Case                     | Radial                                 |
| TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-   | Size / Dimension                   | 0.492" L x 0.236" W (12.50mm x 6.00mm) |
| Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-   | Height - Seated (Max)              | 0.551" (14.00mm)                       |
| Applications General Purpose   Features -   | Termination                        | PC Pins                                |
| Features -  | Lead Spacing                       | 0.295" (7.50mm)                        |
|   | Applications                       | General Purpose                        |
| Report errors?  | Features                           | -                                      |
|   |                                    | Report errors?                         |

### MKP383339040JC02R0 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MKP383339040JC02R0 Payment Methods



If you have any question about MKP383339040JC02R0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com